# Aru NORDIC 92 IN

# **ARU Joinery**

www.arujoinery.com





"Aru Nordic 92 IN" window is a combination of a superb design and energy efficiency. High quality timber profiles and unique 52 mm triple glazing unit offer great protection from cold during winter and heat in summer months, holding back unwanted outside noise at the same time. The owner of "Aru Nordic 92 IN" windows can enjoy excellent product choice without excessive maintenance care for many years







A three-layered window, the bottom frame and sash are protected with aluminium glazing beads. There's an option of using concealed hinges and design. Available a choice of handles.

## **Aru NORDIC 92 IN**



### INWARD OPENING, TILT AND TURN WOODEN WINDOW

Standard window thermal transmittance Uw=0,74 W/m<sup>2</sup>K

### **PROFILE IV92**

92 x 78 mm Jamb: 92 x 78 mm Frame:


Inside groove for windowboard, outside for aluminium cill Aluminium slat on the lower part of the frame

### **FURNITUR**

Fittings: **ROTO NT** Handle: ROTO, HOPPE







### **GLASS**


Triple glazing 52 mm (Ug  $\geq$  0,47 W/m<sup>2</sup>K) Glazing from the inside with wooden glazing beads Fastened with hidden nails, sealed with silicone and seals

### **SEAL**

2-chamber seal surrounding middle frame rebate

with water-based paint or stain


### Handle positions





tilt

microventilation

turn










closed

### **GLAZING BAR OPTIONS**

- 1. Penetrating bars 50 mm
- 2. Bar frame on the hinges
- 3. Taped bars Norwegian style
- 4. Taped bars Georgian style

# 2.



**OPENING:** Inside view

F - FIXED

2x or 3x glazing in the frame. Aluminium slat on the lower part of the frame min measures 330 x 330 mm




DK - TILT AND TURN (LEFT / RIGHT)

min max L=550...1710 mm H=565...2527 mm, weight max 130 kg




D - SIDEHUNG (LEFT / RIGHT)

min max L=550...1710 mm H=565...2527 mm, weight max 130 kg



min max L=550...2510 mm H=565...1327 mm, weight max 80 kg





Round-headed window

