

TECHNICAL DATA E-PRO COLD UNITS

Cold worktop

The E-Pro range of cold units includes various types of refrigerated units and worktops. Thanks to the flexible modular construction, they are easy to combine to create a customised food service system that best suits personal requirements. All units are made of stainless steel and comply with the hygiene standards for professional kitchens.



GENERAL

- Products are designed for the short-term storage of cold food
- All surfaces are made of stainless steel
- Ø63.5mm adjustable feet, with a height adjustment range of -40/+20mm
- GN-sized cupboards and drawers
- Removable slide rails and PVC plastic magnetic gaskets
- Open able transparent plastic lid on top

PERFORMANCE

- The technical features of products are designed to meet the requirements of cold storage in +30°C ambient temperature. The capacity is verified by laboratory experiments
- The temperature can be adjusted between +2 and +6°C
- Refrigerated space for food containers on top, temperature range between +6 and +12°C
- The thermostat control includes a digital temperature display
- The ventilated refrigeration module guarantees even temperature distribution


TECHNICAL FEATURES

- The units have 42mm thick walls, insulating material polyurethane
- CFC and HCFC free
- The refrigerant is R134a
- The refrigeration module is removable without tools and comes with automatic defrost and evaporation of defrost water
- The refrigeration module features an automatic alarm of air-intake filters dirtiness option
- HACCP option is available for all models
- All E-Pro cold units are CE marked



Cold worktop, CDP serie

- Temperature range: **+2...+6°C** (maximum ambient temperature of +30 °C in cold storage)
- Refrigerator modules 1260mm wide model: **C1, C2, C3, CH1**
- Refrigerator modules 1660mm wide model: **CH1**
- Unit modules: **1, 2, 3, 4**



TECHNICAL DATA				
Model	CDP-1-C2-3	CDP-3-C2-3	CDP-1-CH1-1-3	CDP-1-CH1-3-3
External dimensions w x d x h mm	1260x650x970	1260x650x970	1660x650x970	1660x650x970
Temperature range °C	+2...+6	+2...+6	+2...+6	+2...+6
Internal volume dm ³	392	392	542	542
Type of refrigerant, g	R134a, 300	R134a, 300	R134a, 300	R134a, 300
Electrical connection V, Hz	230 1N, 50	230 1N, 50	230 1N, 50	230 1N, 50
Enclosure class	IP44	IP44	IP44	IP44
Connected load W	350	350	750	750
Net weight kg	121	121	160	160
HACCP option	included	included	included	included
Unit volume m ³	1,0	1,0	1,3	1,3
Unit dimensions mm				
height	1050	1050	1050	1050
depth	750	750	750	750
width	1300	1300	1700	1700

Due to continuous product development we reserve the right to technical changes without notice.







MODULES

Refrigerator modules


- C1** Refrigerator module 350W without drawer, temperature range +2...+6°C
- C2** Refrigerator module 350W with a drawer sized GN 1/1 200mm container, temperature range +2...+6°C
- C3** Refrigerator module 350W with two drawers sized for GN 1/1 80 and 100mm containers, temperature range +2...+6°C
- CH1** Refrigerator module 750W without drawer, temperature range +2...+6°C




C1



C2




C3




CH1

Unit modules


- 1** Cupboard with a closed door, two removable shelves and seven pairs of removable shelf brackets
- 2** 2 drawers for bottle baskets or GN 1/1 200mm containers
- 3** 3 drawers for GN 1/1 150mm containers
- 4** 1 drawer for a GN 1/1 150mm container and 3 drawers for GN 1/1 100mm containers




1



2



3



4

