### TECHNICAL DATA E-PRO COLD UNITS

## Refrigerated water dispenser

The E-Pro water dispensers are part of range off food dispensing units. The capacity, materials and technical features of the water dispensers are designed to meet the requirements of professional kitchens.



#### GENERAL

- Made of stainless steel
- Ø63.5mm adjustable feet, with a height adjustment range of -40/+20mm
- E-Pro water dispensers are equipped with a mechanical or optical Oras Electra tap
- Equipped with a water bowl and crate

#### PERFORMANCE

- Maximum water yield 65 litres, and continuous 40 litres per hour
- Cooled water temperature between +3 and +10°C
- 4,5kg ice bank ensures the availability of cooled drinking water in continuous use

#### **TECHNICAL FEATURES**

- Water inlet equipped with a pressure reducer
- Optical models are equipped with a adjustable portion control
- CFC and HCFC free
- Refrigerant R134
- All E-Pro units are CE marked





# Refrigerated water dispenser with a mechanical tap, WDM



TECHNICAL DATA	
Model	WDM
External dimensions w x d x h	450x650x1140
Water yield I/h	65
Water yield in continuous use I/h	40
Ice bank 4.5kg	included
Temperature range °C	+3+10
Type refrigerant, g	R134, 160
Electrical connection V, Hz	230 1N, 50
Connected load W	300
Enclosure class	IP32
Net weight kg	63
Unit volume m <sup>3</sup>	0,5
Unit dimensions mm	
height	1300
width	500
depth	700

Due to continuous product development we reserve the right to technical changes without notice.





TECHNICAL DATA	
Model	WDO
External dimensions w x d x h	450x650x1105
Water yield I/h	65
Water yield in continuous use I/h	40
Ice bank 4.5kg	included
Temperature range °C	+3+10
Type refrigerant, g	R134, 160
Electrical connection V, Hz	230 1N, 50
Connected load W	308
Enclosure class	IP32
Net weight kg	63
Unit volume m <sup>3</sup>	0,5
Unit dimensions mm	
height	1300
width	500
depth	700

Due to continuous product development we reserve the right to technical changes without notice.

