

# ABEM Terrameter LS 2

## RESISTIVITY AND IP IMAGING

Performance through scalability

ABEM Terrameter LS 2 is a world leading resistivity/IP instrument which can be used for a wide range of applications. With an extensive software licensing system it becomes available in multiple configurations, developed to match your requirements. The Terrameter LS 2's latest feature is the IP 100 % duty cycle added for increased measuring speed and improved data quality.

### General

Casing	Rugged aluminum case meets IEC IP66
Computer	Embedded ARM 9, 400 MHz
GPS	Built-in GPS with support for GLONASS
Display	8,4" Active TFT LCD, full colour, daylight visible
I/O ports	2x KPT 32 pin for imaging AUX, Interconnect, USB A, RJ45 for LAN
WLAN	IEEE 802.11 b/g/n, built-in antenna
3G/GSM <sup>1</sup>	3G (UMTS/HSPA+) and GSM (GPRS/Edge), built-in antenna Five bands 3G: 850/800, 900, 1900 and 2100 MHz Quad-band GSM: 850/900/1800/1900 MHz
Measure modes	Resistivity, SP, Resistivity and IP using 50 % or 100 % duty cycle depending on model configuration
Service point	Accessible through Internet
Memory capacity	16 GB, microSD card accessible from outside
Power	12 V, 8 Ah internal battery, built-in charger 12-18 VDC external power
Dimensions	39x21x32 cm (WxLxH)
Weight	13.9 kg, 12.2 kg without internal battery
Ambient temperature range	-20 °C to + 70 °C operating <sup>2, 3</sup> -30 °C to + 80 °C storage <sup>4</sup>

Note 1: Measuring speed may be reduced in high ambient temperature combined with high output power

Note 2: The performance of the LCD is not guaranteed below 0 °C

Note 3: Non-condensing

### Multi-Electrode Survey Systems for 2D & 3D

Number of electrodes	Up to 81, using internal electrode selector Up to 16384, using external electrode selectors
Switching matrix	Internal 10x64, divided into four blocks for effective use of all receiver channels available
Roll-along	Full coverage, both 2D and 3D
Pre-installed array types	Multiple Gradient, Dipole-Dipole, Wenner, Schlumberger, Pole-Dipole and Pole-Pole
Remote electrodes	2 remote electrodes in addition to inline electrodes
Electrode test	Estimates contact resistance on all electrodes currently in use



## Receiver

Number of channels	Up to 12 (+ 2 for transmitter monitoring)
Isolation	All channels are galvanically separated
Input voltage range	Up to $\pm 600$ V
Range	Depending on model $\pm 2.5$ V, $\pm 15$ V, $\pm 600$ V
Input impedance	200 M $\Omega$ ( $\pm 2.5$ V range), 30 M $\Omega$ ( $\pm 15$ V range), 20 M $\Omega$ ( $\pm 600$ V range)
Precision	0.1 %
Accuracy	0.2 %
Resolution	Up to 3 nV at 1 sec integration (theoretical)
Linearity	0.005 %
Flat frequency response	Better than 1 % up to 300 Hz
Full waveform recording	Depending on model Built-in monitoring of all input channels

## Transmitter

Maximum output power	Up to 250 W
Current transmission	Constant current transmitter
Maximum output current	Up to 2500 mA
Maximum output voltage	Up to $\pm 600$ V, 1200 V peak to peak
Current accuracy	0.2 %
Current precision	0.1 %
Instant polarity changer	Yes
Self diagnostics	Monitoring of temperature and power dissipation
Safety	Easily accessible safety switch
Full waveform recording	Depending on model, built-in monitoring of current and voltage output



### Specifications per model

Model Configuration	Basic 2/48	Standard 2/48	Standard 2/81	Advanced 4/48	Advanced 10/48	Advanced 4/81	Advanced 8/81	Advanced 12/81
Number of channels	2	2	2	4	10	4	8	12
Max. number of electrodes	48	48	81	48	48	81	81	81
Input voltage range	$\pm 15$ V	$\pm 15$ V	$\pm 15$ V	$\pm 600$ V	$\pm 600$ V	$\pm 600$ V	$\pm 600$ V	$\pm 600$ V
Input impedance ( $\pm 2.5$ V)	-	-	-	200 M $\Omega$	200 M $\Omega$	200 M $\Omega$	200 M $\Omega$	200 M $\Omega$
Input impedance ( $\pm 15$ V)	30 M $\Omega$	30 M $\Omega$	30 M $\Omega$	30 M $\Omega$	30 M $\Omega$	30 M $\Omega$	30 M $\Omega$	30 M $\Omega$
Input impedance ( $\pm 600$ V)	-	-	20 M $\Omega$	20 M $\Omega$	20 M $\Omega$	20 M $\Omega$	20 M $\Omega$	20 M $\Omega$
Theoretical resolution	22.5 nV	22.5 nV	22.5 nV	3 nV	3 nV	3 nV	3 nV	3 nV
Max. output power	100 W	200 W	200 W	250 W	250 W	250 W	250 W	250 W
Max. output current	1000 mA	2000 mA	2000 mA	2500 mA	2500 mA	2500 mA	2500 mA	2500 mA
Max. output voltage	400 V	500 V	500 V	600 V	600 V	600 V	600 V	600 V
Full waveform recording	No	No	No	Yes	Yes	Yes	Yes	Yes
IP using 100% Duty cycle	No	No	No	Yes	Yes	Yes	Yes	Yes

**ABEM | MALÅ** World Leading Brands

*Guideline Geo is a world-leader in geophysics and geo-technology offering sensors, software, services and support necessary to map and visualize the subsurface. Guideline Geo operates in four international market areas: Infrastructure – examination at start-up and maintenance of infrastructure, Environment – survey of environmental risks and geological hazards, Water – mapping and survey of water supplies and Minerals – efficient exploration. Our offices and regional partners serve clients in 121 countries. The Guideline Geo AB share (GGEO) is listed on NGM Equity.*

**GUIDELINEGEO**

GUIDELINE GEO  
Löfströms Allé 6A  
SE-172 66 Sundbyberg, Sweden  
Tel: +46 8 557 613 00  
info@guidelinegeo.com  
www.guidelinegeo.com

MALÅ GEOSCIENCE  
Skolgatan 11  
SE-930 70 Malå, Sweden  
Tel: +46 953 345 50  
sales@guidelinegeo.com  
www.guidelinegeo.com

ABEM INSTRUMENT  
Löfströms Allé 6A  
SE-172 66 Sundbyberg, Sweden  
Tel: +46 8 564 883 00  
sales@guidelinegeo.com  
www.guidelinegeo.com

MALÅ GEOSCIENCE USA  
465 Deanna Lane  
Charleston 29492, USA  
Tel: +1 843 852 5021  
sales@guidelinegeo.com  
www.guidelinegeo.com