



Aru 78 SOFTLINE IN



The "Aru 78 SOFTLINE IN" window with the angular profile sash and frame is an inward opening wooden window with a profile which is suitable for a modern energy saving building. The larger frame is designed to accommodate triple glazing. This increases insulation values enough for use in a so-called passive house.



A stained pine window.

A three-layered deep-impregnated window, the bottom frame and sash are protected with aluminium glazing beads. There's an option of using concealed hinges and design

Aru 78 SOFTLINE IN



INWARD OPENING, TILT AND TURN VACUUM DEEP-IMPREGNATED WOODEN WINDOW

PROFILE IV78

Jamb: 78 x 78 mm 78 x 78 mm Frame:

Inside groove for windowcill, outside for aluminium cill Aluminium slat on the lower part of the frame

FURNITUR

Fittinas: ROTO NT Handle: ROTO, HOPPE



GLASS

Triple glazing 42 mm (U \geq 0,59 W/m²K) Glazing from the inside with wooden glasing bead Fastened with hidden nails, sealed with silicone


SEAL


2-chamber seal surrounding middle frame rebate

FINISHING

with water-based paint or stain

Handle positions








turn


tilt



GLAZING BAR OPTIONS

- 1. Penetrating bars 50 mm
- 2. Bar frame on the hinges
- 3. Taped bars Norwegian style
- 4. Taped bars Georgian style





OPENING: Inside view

F - FIXED

2x or 3x glazing in the frame. Aluminium slat on the lower part of the frame min measures 330 x 330 mm

DK - TILT AND TURN (LEFT / RIGHT)

min max L=400...1710 mm H=408...2527 mm, weight max 130 kg


D - SIDEHUNG (LEFT / RIGHT)


min max L=400...1710 mm H=408...2527 mm, weight max 130 kg

KIPP - TOPHUNG (Handle above)

min max L=330...2510 mm H=350...1927 mm, weight max 80 kg

NB! Maximum and minimum dimensions and opening possibilities also depend on the apect ratio. Please ask our specialists for additional information.







ት


78

œ

חר









Round-headed window