





Aru Nordic 92 IN Inward opening tilt-and-turn wooden window


- Made to Measure Sizes
- Good thermal performance—Window U_w 0.75 W/m²K of window 1230x1480 mm, glass U_g 0.47
- Frame thickness 92 mm
- Sash profile thickness 92 mm
- Timber selection:
 - fingerjointed or selected laminated pine timber;
 - laminated oak timber
- Timber finishing with waterbased paint or stain. Paint according to RAL color chart, stane according to manufacturer's samples.
- Triple glazing, thickness 52 mm ($U_g > 0,47$)
- Glazing with glazing beads inside, sealing from inside and outside with silicone
- Glazing bar options:
 1. penetrating glazing bars
 2. bar frame on the hinges (outside)
 3. Vienna glazing bars (Norwegian style)
 4. glued-on decorative bars (Georgian style)
 5. decorative bars inside the glass unit




- Extras:
 - jamb extensions, window boards;
 - special glasses (toughened, laminated, sun protection, self cleaning, pattern, etc.), blinds inside the glass unit, different materials and different colors of edge mouldings;
 - concealed hinges, tilt first opening (TF), safety fittings
 - lockable handles, design handles;
 - insect nets
- Various combinations with opening and non-opening parts are possible in single jamb
- Special shape windows




OPENING: Inside view




FIXED (direct glazing)
 Min sizes 330 x 330 mm



Tilt and turn (left/right)
 Min max L= 550...1710 mm H= 566...2527 mm,
 max weight of sash 130 kg




Turn only (left/right)
 Min max L= 550...1710 mm H= 566...2527 mm,
 max weight of sash 130 kg



Tilt only
 Min max L= 550...2500 mm H= 566...1325 mm,
 max weight of sash 80 kg

Handle positions:







Tilt position
 (ventilation)




Turn position
 for quick air
 exchange or window
 washing





Closed




Section without mullion
 Secondary sash/Primary sash



Section through fixed mullion
 Opening sash/Opening sash



Fixed window



Section through mullion
 Opening sash /Fixed light

