





AruAL ED S-78 Nordwin Modern EX Outwards opening Scandinavian type wooden-aluminium external door




- Made to Measure Sizes
- Frame 115x54 mm + aluminium cover
- Sash profile thickness 78 mm
- Gasket around the frame
- Timber selection:
 - frame from fingerjointed, knotted or selected laminated pine timber;
 - threshold from oak timber
 - door leaf from laminated pine or oak timber;
- Timber finishing with waterbased paint or stain. Paint according to RAL colour chart, stain according to manufacturer's samples.
- Aluminium finishing: RAL aluminium colour card
- Triple glazing, thickness 44 mm
- Glazing with glazing beads outside, fastened with hidden nails. Sealed with internal and external gasket.
- Glazing bar options:
 1. penetrating bars
 2. glued on both sides of the glass+slats inside the glazing (Norwegian style)
 3. glued on both sides of the glass (Georgian style)
 4. decorative bars inside the glazing



- Crossbars 115 mm
- Panels:
 - outside: flush aluminium panel
 - inside:
 - flush insulated panel
 - insulated profile panel (vertical/diagonal/herringbone)
 - raised/moulded panel
 - timber panel




- 2D adjustable hinges
- Locking mechanism: ASSA 3-point locks (lower doors ASSA 1-point lock)
- Extras:
 - Jamb extensions, grooves for jamb extension;
 - Special glasses (toughened, laminated, sun protection, self cleaning, pattern etc), various glass spacers
 - Design handles;
 - Different lock-cylinders, serial key cylinders;
 - Door closer or stopper, letter slot, spy-hole, knocker
- Combinations with fixed parts




Standard jamb


Jamb with Groove



Jamb with extension




OPENINGS
Views from outside



LEFT RIGHT

Single door
minimum-maximum
Width 840...1180 mm
Height 1880...2400 mm,
Door leaf weight max 70 kg




LEFT active RIGHT active


Double door
Active part
minimum-maximum
Width 795...1135 mm
Height 1965...2400 mm,
Door leaf weight max 70 kg

Passiive poole
minimum-maximum
Width 395...1135 mm
Height 1965...2400 mm,
Door leaf weight max 70 kg

Middle part of double door



Mullion



Transom

