

Packing presses 100/180P2



Liquid gold


Ergonomics meets efficiency

Our packing presses enable a more efficient pressing process. The pivot operation enables the emptying and filling of the second container during the pressing process. Depending on the desired production quantity, we deliver packing presses in two different sizes: with hourly output of 600 (100P2) or 1,200 kilograms (180P2).

The result is always clear: up to 75% yield with a very low suspension ratio.

The highlights of the 180P2

- All parts that come into contact with the fruit are made of food-grade stainless steel, wood or plastic.
- Simple operation
- Hydraulic cylinders located below—hydraulic oil cannot enter the mash
- Presses with flat position without foundations
- Massive design
- Over-pressure valve
- A press ram subdivided by inserts ensures the juice runs off quickly. This has a high work speed therefore lower oxidation.






The Topseller — 100P2


Everything you need

We can tell you why the 100P2 is so popular with our customers: it is a straightforward investment that pays for itself quickly even with a low number of fruit trees. The excellent production quality and accompanying long lifespan of the machine are additional arguments.

If you can deal with an hourly output of around 600 kilograms, the voran® 100P2 packing press is the right choice. If you need higher performance, you will find the right machine on the following pages.

100P2-compact, high-quality, affordable.







The work horse — 180P2







Packing press 180P2 without lift/lower device



Packing press 180P2 with lift/lower device

Juice collection pan (optional)

Accessory package

Acacia wood or stainless steel press inserts and fabrics made


Packing press 180P2 with lift/lower device






Technical data


100P2



180P2



180P2 with lift/lower device



Туре	100P2	180P2/180P2 inox
Maximum hourly output in I/h	600	1,200
Power consumption in kW	1.5	2.2
Electrical connection*	400 V / 50 Hz (three-phase)	400 V / 50 Hz (three-phase)
Dimensions length/width/height in mm	2,170 / 730 / 1,510	2,250 / 850 / 1,870
Weight in kg	295	1,020
Insert size in cm	50 x 50	65×65
Fabric size in cm	80 x 80	100×100
Design	Steel coated	Steel coated/stainless steel
Delivery scope	18 press fabrics 80 x 80 cm, 20 press inserts 50 x 50 cm**	24 press fabrics 100 x 100 cm, 26 press inserts 65 x 65 cm**

^{*}Other voltages and net specifications on request

^{*}complies with EC 1935/2004 **for 180P2 inox made of stainless steel, otherwise acacia wood



voran

voran.at

How to find us



voran business lines

machines

machine construction

plant construction

facades

voran Maschinen GmbH Sales Linzer Strasse 30

A 4650 Edt bei Lambach T +43(0)72 49 / 444-0 F +43(0)72 49 / 444-888 office@voran.at www.voran.at Production Inn 7 A 4632 Pichl bei Wels Service hotline T +43(0)72 49 / 444-200