

Specification

Modular heterogeneous product.
 Product standard: EN ISO 10582.

CERTIFICATION & CLASSIFICATION	STANDARDS	iD Essential Click
Type of floor covering	EN ISO 10582	Compact Resilient Floorcovering
CE certification		Yes
Classification	EN ISO 10874	Residential: 23 Commercial: 31
TECHNICAL CHARACTERISTICS	STANDARDS	
Total thickness	EN ISO 24346	4.0 mm
Wear layer thickness	EN ISO 24340	0.30 mm
Surface treatment (PUR)		Yes - TopClean™
Bevelled edges		Yes - micro bevel
Total weight	EN ISO 23997	7400 g/m ²
Wear layer binder content	ISO 10582	Type I
Form of delivery	EN ISO 24342	
	Planks Box	18.3 x 122 cm 9 planks/box (= 2.009 m ²)
	Tiles	31 x 60.3 cm 9 tiles/box (= 1.682 m ²)
	ISO 24341 - EN 426 Sheet	-
TECHNICAL PERFORMANCES	STANDARDS	
Dimensional stability	EN ISO 23999	≤ 0.10 %
Reaction to fire	EN 13501-1	B _{f1} -s1 over concrete and wood substrate
Residual indentation	EN ISO 24343-1	≤ 0.08 mm
Furniture leg	EN 424	No damage
Castor chair	ISO 4918	No damage
Underfloor heating		Suitable – max. 27°C
Thermal resistance	ISO 10456	0.03 m ² K/W
Impact sound reduction	EN ISO 717-2	ΔL _w = 5 dB 13 dB with Tarkomfort Pro
Reduction of in room impact noise	NF S31-074	78 dB (Class C - L _{n,e,w} < 85 dB)
Light fastness	EN ISO 105-B02	≥ 6
Resistance to chemicals	EN ISO 26987	High resistance
Slip resistance	EN 13893 DIN 51130	μ ≥ 0.30 DS R9 (tiles) R10 (planks)
Electrical properties	EN 1081	ca. 10 ⁹ Ohm
Colours		8

Technical data in force upon the date of publication (11/15). The values correspond to laboratory tests (no in situ test) and are subject to modification. Tarkett's instructions regarding installation, cleaning and maintenance shall be observed. Please contact your local sales rep. for these instructions.

Our Sustainability tag explains the content of our products and how they contribute to our sustainability strategy and human well-being.

CUSTOMS TARIFF: 482050000000

