

DECLARATION OF PERFORMANCE No.1

CEWOOD SIA / 2025 / CEWOOD Acoustic panels

1. PRODUCT IDENTIFICATION:

CEWOOD acoustic panels - **CW-W** - Factory made wood wool products **WW**

- in extreme fine (0.5 mm), superfine (1.0 mm), fine (1.5 mm) or regular (3.0 mm) wood wool structure;
- natural (unpainted) or painted
- reaction to fire B-s1, d0

2. APPLICATIONS:

Appropriate for **thermal insulation** and **delimiting constructions** according to the technical specification. **Interior works** and decoration, **suspended ceilings** without load. **Sound absorption**.

3. NAME AND ADDRESS OF THE MANUFACTURER:

CEWOOD SIA, Reg. No. LV45403042702

Address: "Galdusalas-1", Jaunlaicene parish, Alūksnes region, LV-4336, Latvia

4. NAME AND ADDRESS OF THE AUTHORISED REPRESENTATIVE:

N/A

5. SYSTEM FOR ASSESSMENT AND VERIFICATION OF CONSTANCY OF PERFORMANCE OF THE PRODUCT (AVCP):

AVCP System **1 and 3**

6. CERTIFICATION STANDARD:

According to standard **EN 13168-2012+A1:2015**

7. CERTIFICATION COMPANY:

INSPECTA LATVIA A/S, NB 1325

Address: Skanstes street 54A, Riga, LV-1013, Latvia

Issued certificate of constancy of performance No. 1325-CPR-3363A

VILNIUS GEDIMINAS TECHNICAL UNIVERSITY, FACULTY OF CIVIL ENGINEERING, INSTITUTE OF BUILDING MATERIALS, LABORATORY OF THERMAL INSULATING MATERIALS AND ACOUSTICS,
NB 1688

Address: Linkmenų street 28, Vilnius, LT-08217, Lithuania

8. DECLARED OPERATIONAL CHARACTERISTICS:

ESSENTIAL CHARACTERISTICS	PERFORMANCE	REFERENCE
Declared thermal resistance		EN 13168:2012+A1+2015
Thickness 15 mm	0,20 m ² ·K/W	
Thickness 25 mm	0,35 m ² ·K/W	
Thickness 35 mm	0,50 m ² ·K/W	
Thickness 50 mm	0,75 m ² ·K/W	
Declared thermal conductivity	0,069 W/m·K	
Reaction to fire	B-s1, d0	
Effects of heat, erosion, ageing/decomposition on thermal resistance stability	15 mm - 0,20 m ² ·K/W	
	25 mm - 0,35 m ² ·K/W	
	35 mm - 0,50 m ² ·K/W	
	50 mm - 0,70 m ² ·K/W	
	0,069 W/m·K	
	Durability properties – no performance determined (NPD)	
Effects of heat, erosion, ageing/decomposition on reaction to fire	Durability properties – no performance determined (NPD)	
Compression		
Thickness 15 mm	CS(10)300	
Thickness 25 mm	CS(10)300	
Thickness 35 mm	CS(10)200	
Thickness 50 mm	CS(10)200	
Bend		
Thickness 15 mm	≥ 1700 kPa	
Thickness 25 mm	≥ 1300 kPa	
Thickness 35 mm	≥ 1000 kPa	
Thickness 50 mm	≥ 700 kPa	
Tensile strength	TR5	
Vapour permeability	MU5	
Water permeability	WS 3	
Compression creep	NPD	

ESSENTIAL CHARACTERISTICS	PERFORMANCE	REFERENCE
Sound absorption. Extended sound absorption coefficient (α_w)	0,50 - 0,90	EN 13168:2012+A1+2015
Release of hazardous substances	NPD	
Continuous smouldering	NPD	

9. *This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3., in accordance with Regulation (EU) No. 305/2011.*

Signed for and on behalf of the manufacturer by:

CEWOOD SIA, Member of board



Ingars Ūdris

Riga, 01.07.2025