

CEWOOD BREEAM International New Construction V6 Scorecard
CEWOOD BREEAM International New Construction V6 Scorecard

BREEAM Category	Issue	Product compliant	Product contributes to a better rating	Product contribution	Evidence	Possible credits
Prerequisite	Legally harvested un traded timber	✓		CEWOOD is certified in accordance with PEFC Trademark rules and Chain of Custody Forest and Trees Based Products and FSC (FSC Mix) certificate for facility and Chain of Custody	PEFC certificate FSC certificate	Prerequisite for certification
Visual comfort	HEA01		✓	CEWOOD Acoustic White panel Light reflection value LRV is more than 70. That positively impacts daylight illuminance.		Up to 4 credits
Indoor air quality	HEA02	✓		Low VOCs emitting material. Product testing done in accordance with EN16516 by independent testing authority. Product is compliant with certifications such as Eurofins Indoor Gold certification.	Declaration of performance	Up to 1 credit Potential exemplary credit
Thermal comfort	HEA04		✓	CEWOOD Acoustic panel can be used for defusing ventilation system as air dispersion layer.	See download site of Producer for information	Up to 2 credits
Acoustic performance	HEA05		✓	Product shows effectiveness in reverberation tests and can provide absorption class A.	Product data sheet Reports	Up to 4 credits
Life cycle impacts	MAT01	✓		Environmental Product Declarations in accordance with ISO 14025 and EN15804 are provided and verified by third party verifier	EPD	Up to 1 credit Potential exemplary credit
Responsible sourcing of construction products	MAT03	✓		CEWOOD panels are produced from FSC Mix certified timber which provides score level "5" for RSCS calculation in accordance with GN18: BREEAM Recognised Responsible Sourcing, Certification Schemes and BREEAM Scheme, Applicability	FSC certificate	Up to 3 credits
Design for durability and resilience	MAT05		✓	CEWOOD panels are provided with information about installation, replacement and recycling. All products are provided with technical data and application possibilities, as well CEWOOD ceiling structures have passed the ball impact tests.	Technical specification General instructions for mounting panels on ceilings	Up to 1 credit
Material efficiency	MAT06		✓	CEWOOD panel estimated service life is 50 years. Panels follows common size ranges for construction materials and multiple possibilities of installation, including re-installation.	See download site of Producer for information	Up to 1 credit
Functional adaptability	WST06		✓	CEWOOD panels can be easily removed, replaced and re-installed.	See download site of Producer for information	Up to 1 credit