

CEWOOD INSPECTION HATCHES

Inspection hatches provide convenient access to building services and technical components located behind ceiling finishes. They allow the necessary inspection, maintenance and repair work to be carried out while preserving a clean and uniform appearance.

Metal inspection hatches

CEWOOD metal inspection hatches combine a durable metal frame with a precisely integrated CEWOOD panel. The surrounding frame section and the hatch door are milled from the same acoustic panel, ensuring that the colour, wood-wool texture and surface pattern match naturally. This creates more consistent joints, improved dimensional accuracy and a cleaner overall appearance.

Suitable for both ceiling and wall applications, the hatches are available in several standard sizes, including fully opening panel options for larger access requirements.



Technical properties

Wood wool width	1.0 mm; other wood wool upon request
Panel thickness	25 mm; 35 mm
Panel size	1200x600 mm; 600x600 mm
Colours	natural painted, white, black, grey and any shade in RAL or NCS system upon request
Profiles	P0; P5; other edge profiles upon request
Fire reaction class	B-s1, d0; A2-s1, d0

Metal inspection hatch specification

Opening mechanism	Push-to-open concealed snap locks
Integrated hatch sizes	300x300 mm; 400x400 mm; 600x400 mm
Full-panel hatch sizes	600x600 mm; 1200x600 mm
Metal frame reaction to fire	A1