

Fermentation and storage tank FD-ZKG

For the fermentation of smaller quantities of beer we recommend the fermentation tank FD-ZKG, a very stable barrel on three legs, entirely made of stainless steel. Its special 3D inner surfaces make cleaning very easy.

The FD-ZKG comes with a serial double jacket. Thus, the producers of bottom-fermented beers for example can directly connect the double jacket to a cooling unit.



APPLICATION RANGE (PRESSURELESS)

> Fermentation

Ideal for

> Maturation

> Beer

> Storage

33

STANDARD EQUIPMENT FERMENTATION AND STORAGE TANK FD-ZKG

- > Tank shell made of AISI304 stainless steel, surface Illd (2R), marbled outside
- > Tank top made of AISI304 stainless steel, surface Illd (2R), marbled outside
- > Vaulted tank top
- > Filling dome on tank top 220 mm LW
- > Lid with drill hole ø 38 mm and removable plastic blank bung to hold the fermentation lock and plug
- > Standing on three legs

RACKING OUTLET

- > Up to a volume of 120 litres internal thread G3/4" with plastic blind plug
- > From a volume of 330 litres onward external thread G1" with plastic-blind cap

BOTTOM OUTLET

- > Up to a volume of 240 litres bottom outlet neck internal thread G3/4" with plastic blank bung
- > From a volume of 330 litres bottom outlet neck external thread G1" with plastic blank bung

DOUBLE JACKET

> Laser welded double jacket for cooling with two connecting nozzle G1" with external thread

TEMPERATURE

> Weld-on thread NW10 DIN 11851 for temperature measuring

DIMENSIONS OF FERMENTATION AND STORAGE TANK FD-ZKG

