



USER MANUAL

For GROVENEER® NATURAL VENEER PRODUCTS

GROVENEER® is a natural high quality oak veneer finished with natural wood oil and has a extremely efficient “peel-and-paste” applying system. For long-term product durability and the desired results, we recommend that you read the following guide.

PRODUCT AND SURFACE PREPARATION

- Smooth the veneer (if necessary). Place the veneer on a flat surface, cover with a smooth plate and apply weight. Allow the veneer to smooth out and acclimatize to the surrounding environment for 36 hours.
- Ideal conditions before, during and after installation are temperatures of 18-27°C (64-80°F) and relative humidity of 35-65%.
- The base must be free of dust and grease, clean, smooth, even and dry. Use only denatured ethyl alcohol to remove grease, dirt, dust and wax. For a smoother surface, sand the surface with sandpaper 280-320 and cover with varnish, primer or paint. Wipe off dust and clean again with denatured ethyl alcohol.
- The product is suitable for indoor use on walls, furniture, doors, interior elements, etc. It is recommended to apply a Groveneer finish similar to the base.
- Groveneer is not suitable for direct contact with uncoated wood, high pressure laminates, melamine surfaces or other plastic surfaces. The installer is responsible for testing each surface to determine if this product is fit for purpose.

INSTALLATION

- Measure the placement and distribution, and mark the mounting location with tape or a washable writing instrument. Be careful and accurate when installing the first panels - this will determine the ease and convenience of all subsequent operations. Don't go, for example, from the edge of the skirting board or the corner of the wall, but move from the horizontal or vertical centre line - the parts of the rooms are never rectangular or 100% straight.
- Remove the backing sheet from the first Groveneer sheet and place it on the mounting plates. The backing sheet can be removed stepwise if desired by positioning the sheet with a non-adhesive portion. The first three to five sheets should not be pressed hard or fully at once, so you can correct the alignment when a misalignment occurs. Do not allow the adhesive to collect debris or dust. Keep your fingers away from the glue.
- A plastic or wooden scraper tool should be used to secure the sheets. Do not use a J-roller! Use a scraper to apply maximum pressure to the surface. It is very important to remove any bubbles and trapped air. Slowly move outwards from the centre to avoid possible air bubbles in the centre of the sheets. Avoid damaging the veneer finish. Repeat the movement until you are sure that the veneer is evenly attached.
- Depending on the quality and tone of the base and the accuracy of installation, cracks may be left between the veneer sheets - fill the cracks with a veneer finish (Soudal, Penosil). Once installed, Groveneer must be finished immediately with a natural wood finish (varnish, wax, oil, etc.) to protect the wood from high humidity. For example, OSMO Oil Wax, Vesting Oil Wax.
- The pressure-sensitive adhesive only reaches its full adhesion within 72 hours after application on suitable surfaces.

PLEASE NOTE!

- This product is for indoor use!
- This is solid wood, a natural material that can react to changes in temperature and humidity and change its size (volume change up to 1mm per 1m). We recommend the product is used in rooms with a stable climate.
- Remember that every installation requires professional care and execution. We encourage buyers to perform tests before using any product at full volume to determine if the product is of acceptable quality and suitable for the particular conditions and purpose.

TOOLS

- Marking: Tape measure; long spirit level or ruler with level; washable pen or tape.
- Cutting: Angle or metal ruler; knife or veneer saw.
- Installation: plastic or wooden scraper tool

CUTTING

- You can easily cut Grovener to size and shape to vary patterns and finishes. Measure out the desired detail, mark the cut line on the veneer, and cut Grovener using a metal ruler and cutter or veneer saw. Use the cutting board and cut on the veneer side. Avoid cuts that damage the veneer and its finish.

CLEANING

- Use a damp microfibre cloth.

MAINTENANCE

- Natural wood care products. For example, Vesting Maintenance Oil, OSMO Maintenance Oil.

LIMITED WARRANTY

The seller warrants that the goods are free from defects in materials and workmanship. The customer assumes full responsibility for the use and results of materials purchased under this agreement. Except as expressly provided herein, the seller makes no warranties, express or implied. The seller's liability under this warranty is limited to the purchase price of the defective material and/or goods.

No credit or claims for material returned to the seller will be permitted until prior written consent has been obtained for such return. The conditions for returning the goods shall be specified upon written consent.

Ninety (90) days from the date such material is shipped, the seller will not accept warranty claims or material return requests.