

IoT eSIM (eUICC)

Plastic 2FF/3FF/4FF

TECHNICAL DATA SHEET


Hardware Features

- Operating temperature: -25 to +85 °C
- Data Retention: 10 years
- Erase/Write Cycles : 100.000 cycles
- 30 Kbytes of User RAM
- Up to 1280 Kbytes of User Flash memory with OTP area
- 1.8 V, 3 V and 5 V supply voltage ranges
- Current consumption compatible with GSM and ETSI specifications
- Power-saving standby state
- Contact assignment compatible with ISO/IEC 7816-2
- ESD protection greater than 4 kV (HBM)

Security Features

- Active shield
- Memory protection unit (MPU)
- Monitoring of environmental parameters
- Protection against faults
- 16- and 32-bit CRC calculation block (ISO 13239, IEEE 802.3, etc.)

GLOBAL IoT CONNECTIVITY



IoT

- True random number generator
- Hardware security-enhanced DES accelerator
- Hardware security-enhanced AES accelerator
- NESCRYPT coprocessor for public key cryptography algorithm

Software features

- 2G/3G Rel12 (U)SIM Main Features
- JavaCard and GlobalPlatform Features
- ISIM Features
- Dynamic Memory Management
- OTA and BIP/CAT-TP Features
- EAP Methods



Fully compliant with GSMA's RSP specifications - SGP.01, SGP.02, SGP.11.

