


20L one-way keg

1. Dimensions/Volume/Weight

Diameter	341 mm
Height	433mm
Volume	20.8 L
Weight (empty keg)	1.9 kg



2. Materials

Inner bag	9 layers laminate, Multi layers high barrier
Valve	POM (food grade)
Spear housing	POM (food grade)
Springs (food contact)	Stainless Steel 304
Springs (non food contact)	Spring steel plated
Seals	TPE (food grade)
Keg	HDPE
Others	HDPE

3. Shelf life

Filled keg	Depends on filled beverage, up to 12 months
O₂ pick up per year	< 0.3 ppm
CO₂ loss per year	<5% (carbonization: 5.5g/L)

4. Mechanical/physical Properties

Operation temperature	0° C~45° C
Maximum dispense pressure	3.5 bar
Maximum pressure	6 bar, free of explosion
Maximum force loading on spear	300 kg
	The Gprokeg is designed to give an extreme low impact on the environment,
Disposal	the empty keg is 100% recyclable, the product is 100% compliant to the EU
	Directive 94/62/EC

5. keg coupler type

S Type	D Type	А Туре	
European Sankey	US Sankey	German Slider	

Technical Specification

6. Food contact

EU food contact approval	All materials and additives used for the components intent to contact with food
	comply with European regulation EU10/2011
FDA	All materials and additives used for the components intent to contact with food
	comply with FDA cfr 175.300
Flavor/taste stability	All materials intent to contact with beverages are free of small molecular migration
	and free of chemical reaction with content of beverages, keeping flavor/taste stability
	of beverages.

7. Palletizing

Empty keg

Pallet size	1200x1000x110mm, one-way
No. of layers	5
Kegs per layer	12
Kegs per pallet	60
Orientation	Upside up
Height	2.26m
Total weight	132kg
Pallets are wrapped with stretch film	

Filled keg

No. of layers	4
Kegs per layer	12
Kegs per pallet	48
Orientation	Upside up
Height	1.88m
Max. layers in warehouse	8

