



TDS 262

INTERIOR

TERRE D'ITALIA PANTHER

Decorative finish made of flakes with 2 colors.

DESCRIPTION

TERRE D'ITALIA PANTHER is the decorative created by merging two different colours of flakes that create an original effect particularly suitable for modern environments. This product is available in 6 different bases and is applied with the special SPALTER DUO tool.

INDICATIONS FOR USE

- Ensure that the substrate is thoroughly dry. In the case of plaster, ensure that it has a curing time of at least 28 days, depending on the temperature.
- Ensure that the substrate has been well prepared and is suitable for painting: dry plaster, having removed any plaster granules, in case of old walls make sure there are no bad or flourey paints, and remove them if necessary, remove flaking paints, etc.

STEP 1

- Apply 1 coat of SCIK PURAL ACRIL primer if necessary.
- Consult the color chart and choose the desired coloration.
- Apply with a brush or roller one or two coats of DECOR FONDO PRIMER diluted with 5-10 % water.
- Allow to dry 12-24 hours.

STEP 2

- Proceed applying TERRE D'ITALIA PANTHER using the special SPALTER DUO tool, which is made up of two SPALTER 70 brushes that allow the simultaneous application of two different colors. Please pay attention to never invert the two brushes with their cans.
- Apply the decoration on the surface in an alternating and uniform way, performing cross movements and mixing the two opalescent colors with different intensity on the whole surface.
- When the product is drying (wait at least 5-10 min), deglaze with the decorative tool SPATULA TD or with the STANLESS STEEL TROWEL.

Stability: 12 months
PH: 7 - 8° C
Voc: 10 gr/l
Specific weight: 1,000

FEATURES: Washable
TOOL: Splater DUO
DRYING TIME: 6 - 8 hours depending on temperature
STORAGE = max. temp. + 30° c - min. temp. + 5° c

PACKAGE	PACKAGE PERFORMANCE	REFERRING PERFORMANCE
L 2,5	10 - 12 mq	1 coat
L 0,750	3 - 4 mq	1 coat



NOTES

- **N.1** Please note that the Specific Weight indicated may not coincide with the Net Package Weight due to technical coloring reasons

- **N.2** Stability period is purely indicative, it refers to the minimum time of stability of the product if stored in good conditions according to the instructions provided, in the original unopened containers and under appropriate temperature conditions. If stored properly, the product may have stability longer than the minimum recommended period.

- **N. 3** Rivedil warrants that the information in this sheet is provided to the best of its technical and scientific experience and knowledge, however, as elements such as weather conditions, labor, tools, quality of third party products and others, outside the direct control of Rivedil, this document does not constitute a warranty, nor does Rivedil authorize its agents and/or representatives to make any kind of warranty based on the information contained in this document. It is advisable to always check the actual suitability of the product for the individual specific case. This cancels and supersedes any previous sheet.

- **N. 4** The raw materials used are natural and may have small differences depending on the batches used. It is therefore recommended to use the same batch of product for the same work to be made. Where this is not possible mix batches together.