

SCHEMA TECNICA N°202

SINFONIA SILVER & GOLD

Special breathable plaster with a final alcantara fabric effect

DESCRIPTION

SINFONIA is a special breathable plaster which reproduce a final alcantara fabric effect.

SINFONIA is available in the following bases: SILVER and GOLD.

The following ready-to-use colors are available for the SILVER base:
RED, VIOLET, WATER, APPLE GREEN, POLAR WHITE.

The ease of application combined with the delicate and refined alcantara effect make this plaster ideal to give a warm touch to both classic and modern environments.

APPLICATION

- The surface to be treated must be dry. Conditions and thickness of the plaster layer affect the drying and hardening time, so make sure it has at least 28 days of curing time, depending on temperature.
- The substrate has to be well prepared and suitable for coating: dry plaster, not any granules from plaster. In case of old walls make sure there is no poor or dusty paint: remove them if necessary as well as flaking paint.
- Apply 1 coat of SCIK PURAL ACRIL insulation if necessary.
- Apply with a brush or roller, one or two coats of DECOR FONDO which has to be thinned up to 5-10 % with water. Allow to dry perfectly, depending on the temperature (from 6 to 12 hours).

APPLICAZIONE A SPATOLA (Spalter application):

- After checking the color chart, add to the base, the quantity of dye necessary to obtain the desired colour.
- Sand as necessary using medium or fine grain sandpaper in order to refine any imperfections.
- Proceed shaving the surface with the coloured plaster SINFONIA, using a stainless steel trowel.
- Allow to dry totally and perfectly (from 6 to 12 hours), then refine any imperfections with glass paper.
- Apply the 2nd coat of SINFONIA following the same procedure.
- Clean the trowel with a sponge smoothing the product just applied on the surface.
- Remove the joint material from the trowel with a clean sponge.
- Repeat this operation in order to recreate light and shadow effects, typical of the alcantara fabric.
- Allow to dry to appreciate the effect.

APPLICAZIONE A RULLO (Roller application):

- After checking the color chart, add to the base, the quantity of dye necessary to obtain the desired colour.
- Dilute the product with 5-10% of water.
- Mix carefully until the base is uniformly colored.
- Apply the colored plaster SINFONIA with a short hair roller over the entire surface.
- After 10-15 minutes, smooth the surface with a SPATOLA TD (TD spalter).
- Allow to dry to appreciate the effect (from 6 to 12 hours).


DECORAZIONI RIVEDIL S.r.l.

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273

P.IVA 03937370751

www.rivedil.com - export@rivedil.com

TECHNICAL DATA	
Nature of the bond	Mineral acrylic plaster and special resins in aqueous solution
Viscosity	
Drying Time	2 h at touch, 6-12 h complete.
Thinning	Ready to use
Yield	3-4m ² /Lt for Trowel;6-7m ² /Lt for Roller
Specific weight	1,166Kg/Lt
Colors	Gold, Silver, Black, Red, Violet, Water, Apple Green, Bordeaux, Polar White
Dry aspect	Alcantara fabric
Wet aspect	Liquid mellow
Storing	Max Temp. +30°C, Min T. +5°C
Stability	2 years (in sealed, unopened original packing)
VOC	30µGr/m ³
TVOC	490µGr/m ³
PH	6-7°C
Cleaning	Water and Soap
Packing	0.750LT,2.5LT
CHARACTERISICS	
Characterisics:	Breathable.
Can be applied on:	Walls,Wood.
for:	Interiors.
Certifications:	
TOOLS AND RELATED PRODUCTS	
Tools:	Stainless Steel Trowel 200x80cm,Stainless Steel Trowel 240x100cm,.
Related products:	DECOR FONDO (WHITE).

NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions . The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge , however , being elements such as weather conditions, labor , tools, quality of third party products and others, not under the direct control of the Rivedil , this document does not constitute a warranty , nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document . We recommend that you always check the suitability of the product to each specific instance . This supersedes all previous editions.

DECORAZIONI RIVEDIL S.r.l.

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273

P.IVA 03937370751

www.rivedil.com - export@rivedil.com