

TDS N°515

SCUDO WOOD

Protective dye, processed with a final wood effect, that might be applied on OXYDA e TRAVERTINO

DESCRIPTION

SCUDO WOOD is a protective dye, processed with a final wood effect, that might be applied on OXYDA e TRAVERTINO, using the special ATTREZZO LEGNO (Wood Tool), available in different sizes (from 10 to 15 cm).

Through this processing and wood color table, different wood textures can be reproduced.

APPLICATION

- The surface to be treated must be dry.
- Apply with a brush or roller, one or two coats of DECOR FONDO which has to be thinned up to 5-10 % with water.
- Apply OXYDA or TRAVERTINO (check related technical data sheets) and process it with the special ATTREZZO LEGNO recreating the texture of a wooden support.
- Allow to dry at least 48h, depending on temperature.
- Using a short-haired roller, proceed with applying evenly, a coat of SCUDO WOOD, which has to be thinned up to 5-10 % with water. Allow to dry for 18-24 hours, depending on the temperature.
- Apply the second coat of SCUDO WOOD, ready to use a allow to dry 18-24 hours, depending on the temperature.

NOTE:

In order to achieve a shaded effect, apply the first coat of SCUDO WOOD, thinned up to 5-10% with water, using a short-haired roller and fade immediately after application using a SPUGNA IN CELLULOSA PURA.

If instead you choose to apply the second coat of SCUDO WOOD, we recommend not to dilute it with water using a SPUGNA IN CELLULOSA PURA. Fade the base to the color tone you want to achieve. Using the second hand is guaranteed better coverage of the surface. You'll also get a darker color than the single-hand application.

Allow the product to dry in any case, respecting the previously mentioned times.

DECORAZIONI RIVEDIL S.r.l.

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273


P.IVA 03937370751

www.rivedil.com - export@rivedil.com

TECHNICAL DATA

Nature of the bond	Acrylic, water based
Viscosity	
Drying Time	24-48 h complete.
Thinning	5-10% 1°mano Water;pronto 2°mano
Yield	9-10m ² /Lt
Specific weight	0,992Kg/Lt
Colors	Ash, Pine, Chestnut, Oak, Light Walnut, Dark Walnut, Douglas, Rosewood, Mahogany, Ebony, Light Gray, Olive Green, Neutral
Dry aspect	glossy/ Matty effect
Wet aspect	Liquid
Storing	Max Temp. +30°C, Min T. +5°C
Stability	2 Years (in sealed, unopened original packing)
VOC	µGr/m ³
TVOC	N/A
PH	N/A
Cleaning	Water
Packing	

CHARACTERISTICS

Characteristics:	Environmentally friendly.
Can be applied on:	Walls.
for:	Interiors/Exteriors.
Certifications:	

TOOLS AND RELATED PRODUCTS

Tools:	.
Related products:	.

CAUTION:

- N.4 The raw materials used are natural and may have minor differences depending on the lots used. It is therefore recommended to use the same batch of product for the same work to be carried out. If this is not possible, mix the batches together.

NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions . The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge , however , being elements such as weather conditions, labor , tools, quality of third party products and others, not under the direct control of the Rivedil , this document does not constitute a warranty , nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document . We recommend that you always check the suitability of the product to each specific instance . This supersedes all previous editions.

DECORAZIONI RIVEDIL S.r.l.

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273

P.IVA 03937370751

www.rivedil.com - export@rivedil.com