



ADSORPTION DEHUMIDIFIER

FOR REMOVAL OF MOISTURE DAMAGE



DRYBOX X2

- Consists of an adsorption fan with an exhaust air duct for moisture-saturated air and two dry air ducts
- The service- area is up to 250 m²
- Capacity up to 19 I / 24 hours
- Energy efficient

- **X2** is an adsorption air dryer to prevent damage in wet rooms.
- X2 consists of a dehumidifier with an exhaust airduct for moisture-saturated air and two air ducts for dry air. The air is sucked into the dehumidifier where it is dehumidified. Moisture-saturated air is carried out through an exhaust air duct to the outside of the building. Dry air circulates via the two dry air ducts. No collection container for liquid is needed.
- X2 can dehumidify spaces of up to 250 m².
- X2 has a dehumidification capacity of 19 I / 24 hours.

TECHNICAL DATA

Dry air volume 250 m³/h Wet air volume 35 m³/h 1 x 63 mm/1 x 100 mm Dry air emissions Wet air emissions 63 mm Up till 250 m² Noise level (3m) 52 dB Weight 11 Kg Height x width x depth 285 x 335 x 425 Dehumidifying capacityt 19 I/24 hours Connection 230V/ 50Hz 805W Load Filter Inside change

Installation set


Dry air duct Ø 63 mm x 6 meter

Dry air duct Ø 100 mm x 6 meter

Wet air duct Ø 63 mm x 1,5 meter

Air filter 2-pack

Connection plate 1 pcs



Install the dry air ducts & the exhaust air duct according to the sketch.

Attach the exhaust duct to the air valve.

AMROX GROUP AB (Mätforum AB) TEL:08-82 25 50

RESELLER

Riit trading OÜ Phone:+372 5094 786 E-mail:riit.tarmo@riittrading.com www.riittrading.com

