

# BARIS 40 LED BRACKET

GENERAL CARD



## TECHNICAL PARAMETERS

<b>Rated power of the luminaire [W]*:</b>	7.00 - 39.00
<b>Luminous flux [lm]*:</b>	550 - 4450
<b>Colour temperature [K]:</b>	3000; 4000
<b>Ingress protection:</b>	IP44
<b>Impact resistance:</b>	IK03
<b>Material of the body:</b>	aluminium
<b>Colour of the body:</b>	black; grey; white
<b>Diffuser material:</b>	PC; PS
<b>Diffuser type:</b>	OPAL; PRM
<b>Mounting version:</b>	surface, wall mounted
<b>Dimensions (H/W/T/S) [mm]:</b>	53/71/579; 53/71/860;
<b>Warranty [years]:</b>	5

## CHARACTERISTICS

A luminaire with a very narrow cross-section. The bodies are available as an anodised aluminium profile in grey or as an aluminium profile painted in white or black (other colours available on request). Optical system in the form of an opal cover. The optical system in the form of a prismatic diaphragm reduces glare and is characterized by a greater light transmittance than the opal diffuser, which has a direct impact on a higher value of luminous efficacy.

## APPLICATION

The unique design predisposes these luminaires to illuminate: offices, conference rooms, and other representative spaces, in offices, passageways, sanitary rooms, and bathrooms (wall lamps), in public utility buildings.

Versions marked "VD" are only intended for use in traffic zones and corridors inside buildings included in Table 5.1 of EN12464.

# BARIS 40 LED BRACKET

GENERAL CARD

## AVAILABLE VERSIONS



Click index >>, to see details

### BARIS 40 LED BRACKET

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Colour of the body	DIMM DALI	Dimensions (H/W/T/S) [mm]	Index
7	3000	550	OPAL	grey		53/71/579	<a href="#">&gt;&gt; 675430</a>
7	3000	550	OPAL	white		53/71/579	<a href="#">&gt;&gt; 675423</a>
7	3000	550	OPAL	black		53/71/579	<a href="#">&gt;&gt; 675409</a>
7	4000	600	OPAL	grey		53/71/579	<a href="#">&gt;&gt; 675454</a>
7	4000	600	OPAL	white		53/71/579	<a href="#">&gt;&gt; 675447</a>
7	4000	600	OPAL	black		53/71/579	<a href="#">&gt;&gt; 675416</a>

### BARIS 40 LED BRACKET 13W

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Colour of the body	DIMM DALI	Dimensions (H/W/T/S) [mm]	Index
13	3000	1300	OPAL	grey	yes	53/71/860	<a href="#">&gt;&gt; 674037</a>
13	3000	1300	OPAL	white	yes	53/71/860	<a href="#">&gt;&gt; 675164</a>
13	3000	1300	OPAL	black	yes	53/71/860	<a href="#">&gt;&gt; 674808</a>
13	3000	1300	OPAL	grey		53/71/860	<a href="#">&gt;&gt; 674013</a>
13	3000	1300	OPAL	white		53/71/860	<a href="#">&gt;&gt; 675140</a>
13	3000	1300	OPAL	black		53/71/860	<a href="#">&gt;&gt; 674785</a>
13	4000	1400	OPAL	grey	yes	53/71/860	<a href="#">&gt;&gt; 674006</a>
13	4000	1400	OPAL	white	yes	53/71/860	<a href="#">&gt;&gt; 675133</a>
13	4000	1400	OPAL	black	yes	53/71/860	<a href="#">&gt;&gt; 674778</a>
13	4000	1400	OPAL	grey		53/71/860	<a href="#">&gt;&gt; 455865</a>
13	4000	1400	OPAL	white		53/71/860	<a href="#">&gt;&gt; 675003</a>
13	4000	1400	OPAL	black		53/71/860	<a href="#">&gt;&gt; 674648</a>
13	3000	1500	PRM	grey	yes	53/71/860	<a href="#">&gt;&gt; 674044</a>
13	3000	1500	PRM	white	yes	53/71/860	<a href="#">&gt;&gt; 675171</a>
13	3000	1500	PRM	black	yes	53/71/860	<a href="#">&gt;&gt; 674815</a>
13	3000	1500	PRM	grey		53/71/860	<a href="#">&gt;&gt; 674020</a>
13	3000	1500	PRM	white		53/71/860	<a href="#">&gt;&gt; 675157</a>
13	3000	1500	PRM	black		53/71/860	<a href="#">&gt;&gt; 674792</a>
13	4000	1600	PRM	grey	yes	53/71/860	<a href="#">&gt;&gt; 455872</a>
13	4000	1600	PRM	white	yes	53/71/860	<a href="#">&gt;&gt; 675010</a>
13	4000	1600	PRM	black	yes	53/71/860	<a href="#">&gt;&gt; 674655</a>
13	4000	1600	PRM	grey		53/71/860	<a href="#">&gt;&gt; 455964</a>
13	4000	1600	PRM	white		53/71/860	<a href="#">&gt;&gt; 675102</a>
13	4000	1600	PRM	black		53/71/860	<a href="#">&gt;&gt; 674747</a>

# BARIS 40 LED BRACKET

## GENERAL CARD

### BARIS 40 LED BRACKET 16W

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Colour of the body	DIMM DALI	Dimensions (H/W/T/S) [mm]	Index
16	3000	1300	OPAL	grey	yes	53/71/579	<a href="#">&gt;&gt; 318955</a>
16	3000	1300	OPAL	white	yes	53/71/579	<a href="#">&gt;&gt; 318993</a>
16	3000	1300	OPAL	black	yes	53/71/579	<a href="#">&gt;&gt; 319037</a>
16	3000	1300	OPAL	grey		53/71/579	<a href="#">&gt;&gt; 318931</a>
16	3000	1300	OPAL	white		53/71/579	<a href="#">&gt;&gt; 318979</a>
16	3000	1300	OPAL	black		53/71/579	<a href="#">&gt;&gt; 319013</a>
16	4000	1400	OPAL	grey	yes	53/71/579	<a href="#">&gt;&gt; 318948</a>
16	4000	1400	OPAL	white	yes	53/71/579	<a href="#">&gt;&gt; 318986</a>
16	4000	1400	OPAL	black	yes	53/71/579	<a href="#">&gt;&gt; 319020</a>
16	4000	1400	OPAL	grey		53/71/579	<a href="#">&gt;&gt; 318924</a>
16	4000	1400	OPAL	white		53/71/579	<a href="#">&gt;&gt; 318962</a>
16	4000	1400	OPAL	black		53/71/579	<a href="#">&gt;&gt; 319006</a>
16	3000	1600	PRM	grey	yes	53/71/579	<a href="#">&gt;&gt; 455445</a>
16	3000	1600	PRM	white	yes	53/71/579	<a href="#">&gt;&gt; 455483</a>
16	3000	1600	PRM	black	yes	53/71/579	<a href="#">&gt;&gt; 455520</a>
16	3000	1600	PRM	grey		53/71/579	<a href="#">&gt;&gt; 455421</a>
16	3000	1600	PRM	white		53/71/579	<a href="#">&gt;&gt; 455469</a>
16	3000	1600	PRM	black		53/71/579	<a href="#">&gt;&gt; 455506</a>
16	4000	1700	PRM	grey	yes	53/71/579	<a href="#">&gt;&gt; 455438</a>
16	4000	1700	PRM	white	yes	53/71/579	<a href="#">&gt;&gt; 455476</a>
16	4000	1700	PRM	black	yes	53/71/579	<a href="#">&gt;&gt; 455513</a>
16	4000	1700	PRM	grey		53/71/579	<a href="#">&gt;&gt; 455414</a>
16	4000	1700	PRM	white		53/71/579	<a href="#">&gt;&gt; 455452</a>
16	4000	1700	PRM	black		53/71/579	<a href="#">&gt;&gt; 455490</a>

### BARIS 40 LED BRACKET 39W

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Colour of the body	DIMM DALI	Dimensions (H/W/T/S) [mm]	Index
39	3000	3600	OPAL	grey	yes	53/71/860	<a href="#">&gt;&gt; 674099</a>
39	3000	3600	OPAL	white	yes	53/71/860	<a href="#">&gt;&gt; 675225</a>
39	3000	3600	OPAL	black	yes	53/71/860	<a href="#">&gt;&gt; 674860</a>
39	3000	3600	OPAL	grey		53/71/860	<a href="#">&gt;&gt; 674075</a>
39	3000	3600	OPAL	white		53/71/860	<a href="#">&gt;&gt; 675201</a>
39	3000	3600	OPAL	black		53/71/860	<a href="#">&gt;&gt; 674846</a>
39	4000	3900	OPAL	grey	yes	53/71/860	<a href="#">&gt;&gt; 674051</a>
39	4000	3900	OPAL	white	yes	53/71/860	<a href="#">&gt;&gt; 675188</a>
39	4000	3900	OPAL	black	yes	53/71/860	<a href="#">&gt;&gt; 674822</a>

# BARIS 40 LED BRACKET

## GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Colour of the body	DIMM DALI	Dimensions (H/W/T/S) [mm]	Index
39	4000	3900	OPAL	grey		53/71/860	<a href="#">&gt;&gt; 455957</a>
39	4000	3900	OPAL	white		53/71/860	<a href="#">&gt;&gt; 675096</a>
39	4000	3900	OPAL	black		53/71/860	<a href="#">&gt;&gt; 674730</a>
39	3000	4150	PRM	grey	yes	53/71/860	<a href="#">&gt;&gt; 674105</a>
39	3000	4150	PRM	white	yes	53/71/860	<a href="#">&gt;&gt; 675232</a>
39	3000	4150	PRM	black	yes	53/71/860	<a href="#">&gt;&gt; 674877</a>
39	3000	4150	PRM	grey		53/71/860	<a href="#">&gt;&gt; 674082</a>
39	3000	4150	PRM	white		53/71/860	<a href="#">&gt;&gt; 675218</a>
39	3000	4150	PRM	black		53/71/860	<a href="#">&gt;&gt; 674853</a>
39	4000	4450	PRM	grey	yes	53/71/860	<a href="#">&gt;&gt; 674068</a>
39	4000	4450	PRM	white	yes	53/71/860	<a href="#">&gt;&gt; 675195</a>
39	4000	4450	PRM	black	yes	53/71/860	<a href="#">&gt;&gt; 674839</a>
39	4000	4450	PRM	grey		53/71/860	<a href="#">&gt;&gt; 455971</a>
39	4000	4450	PRM	white		53/71/860	<a href="#">&gt;&gt; 675119</a>
39	4000	4450	PRM	black		53/71/860	<a href="#">&gt;&gt; 674754</a>

## BARIS 40 LED BRACKET VD 15W

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Colour of the body	DIMM DALI	Dimensions (H/W/T/S) [mm]	Index
15	4000	1100	OPAL	grey		53/71/579	<a href="#">&gt;&gt; 319044</a>
15	4000	1100	OPAL	white		53/71/579	<a href="#">&gt;&gt; 319068</a>
15	4000	1100	OPAL	black		53/71/579	<a href="#">&gt;&gt; 319082</a>
15	4000	1350	PRM	grey		53/71/579	<a href="#">&gt;&gt; 455537</a>
15	4000	1350	PRM	white		53/71/579	<a href="#">&gt;&gt; 455544</a>
15	4000	1350	PRM	black		53/71/579	<a href="#">&gt;&gt; 455551</a>

Card creation date: 22 November 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 07/2022; 240/2023; 241/2023; 242/2023