

BARIS SQUARE 40 LED

GENERAL CARD



TECHNICAL PARAMETERS

Rated power of the luminaire [W]*:	32.00 - 116.00
Luminous flux [lm]*:	3200 - 11700
Supply voltage [V]:	220-240
Frequency [Hz]:	50-60
Energy efficiency class:	E; F
Electrical protection class:	I
Colour temperature [K]:	3000; 4000
Diffuser type:	OPAL; clear
Material of the body:	aluminium
Colour of the body:	black; grey; white
Impact resistance:	IK06
Ingress protection:	IP20

CHARACTERISTICS

Baris Square 40 Led is a striking pendant lamp. Its classic shape fits perfectly into modern design. The lamp body is made of anodized aluminum profile in gray or aluminum profile painted in white or black (other colors available on request). The lamp is offered with two types of lampshade - prismatic or milky. The availability of the lamp in three sizes allows you to design the distribution of lighting in an individually tailored way. Lamps of different sizes and hung at different lengths can create an unlimited number of lighting compositions in the room.

APPLICATION

The lamp is dedicated for indoor use. It is used as a source of main light in representative rooms, hotels, restaurants, conference rooms. Unique design and energy-saving LED modules also dedicate the lamp for use in modern office buildings.

BARIS SQUARE 40 LED

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

Baris SQUARE 40 LED 1162/1162/52mm

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Diffuser colour	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
65	6500	3000	milky	black	1162/1162/52	>> 939167
65	6500	3000	milky	black	1162/1162/52	>> 938962
65	6500	3000	prismatic	black	1162/1162/52	>> 939044
65	6500	3000	prismatic	black	1162/1162/52	>> 938849
65	7000	4000	milky	black	1162/1162/52	>> 938764
65	7000	4000	milky	white	1162/1162/52	>> 939266
65	7000	4000	milky	black	1162/1162/52	>> 938566
65	7000	4000	milky	grey	1162/1162/52	>> 939273
65	7000	4000	prismatic	black	1162/1162/52	>> 938641
65	7000	4000	prismatic	black	1162/1162/52	>> 938108
116	10900	3000	milky	black	1162/1162/52	>> 939150
116	10900	3000	milky	black	1162/1162/52	>> 938955
116	10900	3000	prismatic	black	1162/1162/52	>> 939099
116	10900	3000	prismatic	black	1162/1162/52	>> 938894
116	11700	4000	milky	black	1162/1162/52	>> 938757
116	11700	4000	prismatic	white	1162/1162/52	>> 939242
116	11700	4000	milky	black	1162/1162/52	>> 938559
116	11700	4000	milky	grey	1162/1162/52	>> 939259
116	11700	4000	prismatic	black	1162/1162/52	>> 938696
116	11700	4000	prismatic	black	1162/1162/52	>> 938214

Baris SQUARE 40 LED 602/602/52mm

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Diffuser colour	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
32	3200	3000	milky	black	602/602/52	>> 938528
32	3200	3000	milky	black	602/602/52	>> 938504
32	3200	3000	prismatic	black	602/602/52	>> 938511
32	3200	3000	prismatic	black	602/602/52	>> 938498
32	3450	4000	milky	black	602/602/52	>> 938443
32	3450	4000	milky	black	602/602/52	>> 938405
32	3450	4000	prismatic	black	602/602/52	>> 938436
32	3450	4000	prismatic	black	602/602/52	>> 938085
56	5300	3000	milky	black	602/602/52	>> 938351
56	5300	4000	milky	black	602/602/52	>> 938337
56	5300	3000	prismatic	black	602/602/52	>> 938344

BARIS SQUARE 40 LED

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Diffuser colour	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
56	5300	4000	prismatic	black	602/602/52	>> 938320
56	5700	4000	milky	black	602/602/52	>> 938313
56	5700	4000	prismatic	white	602/602/52	>> 939228
56	5700	4000	milky	black	602/602/52	>> 938276
56	5700	4000	milky	grey	602/602/52	>> 939235
56	5700	4000	prismatic	black	602/602/52	>> 938306
56	5700	4000	prismatic	black	602/602/52	>> 938191

Baris SQUARE 40 LED 882/882/52mm

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Diffuser colour	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
48	4800	3000	milky	black	882/882/52	>> 939143
48	4800	3000	milky	black	882/882/52	>> 938948
48	4800	3000	prismatic	black	882/882/52	>> 939037
48	4800	3000	prismatic	black	882/882/52	>> 938832
48	5150	4000	milky	black	882/882/52	>> 938740
48	5150	4000	prismatic	white	882/882/52	>> 939341
48	5150	4000	milky	black	882/882/52	>> 938542
48	5150	4000	milky	grey	882/882/52	>> 939358
48	5150	4000	prismatic	black	882/882/52	>> 938634
48	5150	4000	prismatic	black	882/882/52	>> 938092
86	8150	3000	milky	black	882/882/52	>> 939136
86	8150	3000	milky	black	882/882/52	>> 938931
86	8150	3000	prismatic	black	882/882/52	>> 939082
86	8150	3000	prismatic	black	882/882/52	>> 938887
86	8750	4000	milky	black	882/882/52	>> 938733
86	8750	4000	milky	white	882/882/52	>> 939327
86	8750	4000	milky	black	882/882/52	>> 938535
86	8750	4000	milky	grey	882/882/52	>> 939334
86	8750	4000	prismatic	black	882/882/52	>> 938689
86	8750	4000	prismatic	black	882/882/52	>> 938207

Card creation date: 22 June 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 80/2022