GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP54	
Impact resistance:	IK10	
Nominal power [W]:	12.00; 14.00	
Luminous flux [lm]*:	950; 1600	
Colour temperature [K]:	4000	
SDCM:	≤ 5	
Energy efficiency class:	E; F	
Material of the body:	PP	
Diffuser material:	PC	
Diffuser type:	OPAL	
Optics material:	PC	
Mounting version:	surface	
Dimensions (H/W/T/S) [mm]:) [mm]: Ø280/72; 280/72;	

CHARACTERISTICS

Surface-mounted, round LED light fitting with a luminous flux of 87 lm/W, ingress protection class IP54 and an integrated energysaving light source LED. White base; diffuser made of impactresistant PC provides even light distribution and ensures a high impact resistance class (IK10).

APPLICATION

Surface mounted fitting intended for indoor use in representative rooms and passageways (large conference halls, hotel corridors, studies). Designed for mounting on ceilings and walls. Wide range of diameters and two diffuser versions allow for the same fitting to be used in rooms with different parameters. Well suited to be used as a basic or general interior light source.



GAMMA LED

GENERAL CARD


AVAILABLE VERSIONS

				Click	index >>, to see details
Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Motion sensor	Index
12	4000	950	OPAL		<u>>> 226748</u>
14	4000	1600	OPAL		<u>>> 226663</u>
12	4000	950	OPAL	yes	<u>>> 226755</u>
12	4000	950	OPAL	yes	<u>>> 226755/H</u>
14	4000	1600	OPAL	yes	<u>>> 226670</u>
14	4000	1600	OPAL	yes	<u>>> 226670/H</u>



GENERAL CARD

LUMINOUS INTENSITY DISTRIB. CURVE



GAMMA LED

Card creation date: 01 August 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10% CE Certificate CE - Nr: 166/2020; 392/2023

A This product is a subject to electric and electronic waste equipment regulations (WEEE).

