



## TECHNICAL PARAMETERS

---

<b>Rated power [W] - range:</b>	21-37; 32-55
<b>Luminous flux of the luminaire [lm] - range:</b>	2000 - 3800; 3100 - 5600
<b>Electrical protection class:</b>	I
<b>Colour temperature [K]:</b>	3000; 4000
<b>Colour rendering index:</b>	>80
<b>SDCM:</b>	≤ 3
<b>Diffuser material:</b>	PMMA
<b>Diffuser type:</b>	OPAL
<b>Diffuser colour:</b>	white
<b>Dimensions (H/W/T/S) [mm]:</b>	630/50; 970/80;
<b>Ingress protection:</b>	IP40
<b>Mounting version:</b>	suspended
<b>Warranty [years]:</b>	5

## CHARACTERISTICS

---

Sizzano is a suspended ring-shaped LED luminaire, whose shape and final form are given by an impact-resistant diffuser made by rotomoulding. The design is complemented by an inner collar in black or any RAL color to match the character and color scheme of the room.

## APPLICATION

---

The classic proportions of Sizzano will emphasize the prestigious character of any room without the effect of tactless domination. The length of the pendant can be adjusted to individual needs and the desired final effect. The complete adjustable suspension system with the central box is supplied with the luminaire.

Multi LED versions allow the selection of 4 luminaire power and flux settings, increasing the versatility and functionality of the luminaire and reducing the number of indexes to the minimum.

## AVAILABLE VERSIONS



Click index >>, to see details

### Sizzano 630/50mm

Rated power [W] - range	Luminous flux of the luminaire [lm] - range	Colour temperature [K]	DIMM DALI	Dimensions (H/W/T/S) [mm]	Index
21-37	2100 - 3600	3000		630/50	<a href="#">&gt;&gt; 468063</a>
21-37	2200 - 3800	4000		630/50	<a href="#">&gt;&gt; 468001</a>
27	2600	3000	yes	630/50	<a href="#">&gt;&gt; 468070</a>
27	2800	4000	yes	630/50	<a href="#">&gt;&gt; 468018</a>
37	3600	3000	yes	630/50	<a href="#">&gt;&gt; 468087</a>
37	3800	4000	yes	630/50	<a href="#">&gt;&gt; 468025</a>

### Sizzano 970/80mm

Rated power [W] - range	Luminous flux of the luminaire [lm] - range	Colour temperature [K]	DIMM DALI	Dimensions (H/W/T/S) [mm]	Index
32-55	3000 - 5300	3000		970/80	<a href="#">&gt;&gt; 468094</a>
32-55	3200 - 5600	4000		970/80	<a href="#">&gt;&gt; 468032</a>
40	4000	3000	yes	970/80	<a href="#">&gt;&gt; 468100</a>
40	4200	4000	yes	970/80	<a href="#">&gt;&gt; 468049</a>
55	5300	3000	yes	970/80	<a href="#">&gt;&gt; 468117</a>
55	5600	4000	yes	970/80	<a href="#">&gt;&gt; 468056</a>

Card creation date: 29 March 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 216/2023