



## TECHNICAL PARAMETERS

<b>Ingress protection:</b>	IP20
<b>Rated power [W] - range:</b>	30-53
<b>Luminous flux of the luminaire [lm] - range:</b>	1890 - 6100
<b>Colour temperature [K]:</b>	3000; 4000
<b>Colour temperature [K] - range:</b>	2700 - 6500
<b>Frequency [Hz]:</b>	50 - 60
<b>SDCM:</b>	≤ 3
<b>Colour rendering index:</b>	>80
<b>Electrical protection class:</b>	I
<b>Diffuser material:</b>	PMMA; PS
<b>Diffuser type:</b>	OPAL
<b>Colour of the body:</b>	black; white
<b>Dimensions (H/W/T/S) [mm]:</b>	ø602/32; ø602/68; ø900/32; ø900/68; ø1200/32
<b>Mounting version:</b>	surface; suspended
<b>Warranty [years]:</b>	5

## CHARACTERISTICS

Suspended or surface-mounted ring-shaped LED luminaire, allowing for an attractive arrangement of representative interiors. The luminaire is made of steel powder coated in white, black or other color to fit the character of the interior. The milky diffuser made with thermoforming method emphasises the decorative character of the luminaire. The pendant option includes a complete pendant system with a central box.

Multi LED versions allow you to choose from 4 flux and power settings increasing the versatility and functionality of the luminaire, while reducing the number of indexes to the necessary minimum.

## APPLICATION

SOLANTO is an extremely glamorous pendant or surface mounted luminaire, dedicated to such interiors as lobbies, receptions, shopping malls, showrooms. It can be also used in apartments and apartments, perfectly fitting into stylish surroundings.

# SOLANTO

## GENERAL CARD

### AVAILABLE VERSIONS



Click index >>, to see details

#### SOLANTO surface

Rated power [W] - range	Colour temperature [K]	Luminous flux of the luminaire [lm] - range	Colour of the body	DIMM DALI	Dimensions (H/W/T/S) [mm]	Mounting version	Index
30/38/45/53	3000	1890/2400/2800/3330	black		ø602/68	surface	<a href="#">&gt;&gt; 463136</a>
30/38/45/53	4000	2040/2600/3000/3600	black		ø602/68	surface	<a href="#">&gt;&gt; 463129</a>
30/38/45/53	3000	2550/3200/3800/4500	white		ø602/68	surface	<a href="#">&gt;&gt; 463013</a>
30/38/45/53	4000	2820/3570/4200/4980	white		ø602/68	surface	<a href="#">&gt;&gt; 463006</a>
30/38/45/53	3000	1890/2400/2800/3330	black		ø900/68	surface	<a href="#">&gt;&gt; 463372</a>
30/38/45/53	4000	2040/2600/3000/3600	black		ø900/68	surface	<a href="#">&gt;&gt; 463365</a>
30/38/45/53	3000	2550/3200/3800/4500	white		ø900/68	surface	<a href="#">&gt;&gt; 463259</a>
30/38/45/53	4000	2820/3570/4200/4980	white		ø900/68	surface	<a href="#">&gt;&gt; 463242</a>
38	3000	2400	black	yes	ø602/68	surface	<a href="#">&gt;&gt; 463150</a>
38	4000	2590	black	yes	ø602/68	surface	<a href="#">&gt;&gt; 463143</a>
38	3000	3230	white	yes	ø602/68	surface	<a href="#">&gt;&gt; 463037</a>
38	4000	3570	white	yes	ø602/68	surface	<a href="#">&gt;&gt; 463020</a>
38	3000	2400	black	yes	ø900/68	surface	<a href="#">&gt;&gt; 463396</a>
38	4000	2590	black	yes	ø900/68	surface	<a href="#">&gt;&gt; 463389</a>
38	3000	3230	white	yes	ø900/68	surface	<a href="#">&gt;&gt; 463273</a>
38	4000	3570	white	yes	ø900/68	surface	<a href="#">&gt;&gt; 463266</a>
53	3000	3340	black	yes	ø602/68	surface	<a href="#">&gt;&gt; 463174</a>
53	4000	3600	black	yes	ø602/68	surface	<a href="#">&gt;&gt; 463167</a>
53	3000	4500	white	yes	ø602/68	surface	<a href="#">&gt;&gt; 463051</a>
53	4000	4980	white	yes	ø602/68	surface	<a href="#">&gt;&gt; 463044</a>
53	3000	3340	black	yes	ø900/68	surface	<a href="#">&gt;&gt; 463419</a>
53	4000	3600	black	yes	ø900/68	surface	<a href="#">&gt;&gt; 463402</a>
53	3000	4500	white	yes	ø900/68	surface	<a href="#">&gt;&gt; 463297</a>
53	4000	4980	white	yes	ø900/68	surface	<a href="#">&gt;&gt; 463280</a>

#### SOLANTO suspended

Rated power [W] - range	Colour temperature [K]	Luminous flux of the luminaire [lm] - range	Colour of the body	DIMM DALI	Dimensions (H/W/T/S) [mm]	Mounting version	Index
30/38/45/53	3000	1890/2400/2800/3330	black		ø602/32	suspended	<a href="#">&gt;&gt; 463198</a>
30/38/45/53	4000	2040/2600/3000/3600	black		ø602/32	suspended	<a href="#">&gt;&gt; 463181</a>
30/38/45/53	3000	2550/3200/3800/4500	white		ø602/32	suspended	<a href="#">&gt;&gt; 463075</a>
30/38/45/53	4000	2820/3570/4200/4980	white		ø602/32	suspended	<a href="#">&gt;&gt; 463068</a>
30/38/45/53	3000	1890/2400/2800/3330	black		ø900/32	suspended	<a href="#">&gt;&gt; 463433</a>
30/38/45/53	4000	2040/2600/3000/3600	black		ø900/32	suspended	<a href="#">&gt;&gt; 463426</a>

# SOLANTO

## GENERAL CARD

Rated power [W] - range	Colour temperature [K]	Luminous flux of the luminaire [lm] - range	Colour of the body	DIMM DALI	Dimensions (H/W/T/S) [mm]	Mounting version	Index
30/38/45/53	3000	2550/3200/3800/4500	white		ø900/32	suspended	<a href="#">&gt;&gt; 463310</a>
30/38/45/53	4000	2820/3570/4200/4980	white		ø900/32	suspended	<a href="#">&gt;&gt; 463303</a>
38	3000	2400	black	yes	ø602/32	suspended	<a href="#">&gt;&gt; 463211</a>
38	4000	2590	black	yes	ø602/32	suspended	<a href="#">&gt;&gt; 463204</a>
38	3000	3230	white	yes	ø602/32	suspended	<a href="#">&gt;&gt; 463099</a>
38	4000	3570	white	yes	ø602/32	suspended	<a href="#">&gt;&gt; 463082</a>
38	3000	2400	black	yes	ø900/32	suspended	<a href="#">&gt;&gt; 463457</a>
38	4000	2590	black	yes	ø900/32	suspended	<a href="#">&gt;&gt; 463440</a>
38	3000	3230	white	yes	ø900/32	suspended	<a href="#">&gt;&gt; 463334</a>
38	4000	3570	white	yes	ø900/32	suspended	<a href="#">&gt;&gt; 463327</a>
53	3000	4700	black	yes	ø602/32	suspended	<a href="#">&gt;&gt; 463235</a>
53	4000	4700	black	yes	ø602/32	suspended	<a href="#">&gt;&gt; 463228</a>
53	3000	6100	white	yes	ø602/32	suspended	<a href="#">&gt;&gt; 463112</a>
53	4000	6100	white	yes	ø602/32	suspended	<a href="#">&gt;&gt; 463105</a>
53	3000	3340	black	yes	ø900/32	suspended	<a href="#">&gt;&gt; 463471</a>
53	4000	3600	black	yes	ø900/32	suspended	<a href="#">&gt;&gt; 463464</a>
53	3000	4500	white	yes	ø900/32	suspended	<a href="#">&gt;&gt; 463358</a>
53	4000	4980	white	yes	ø900/32	suspended	<a href="#">&gt;&gt; 463341</a>
62	3000	3900	black	yes	ø1200/32	suspended	<a href="#">&gt;&gt; 467974</a>
62	3000	3900	black		ø1200/32	suspended	<a href="#">&gt;&gt; 467936</a>
62	4000	4300	black	yes	ø1200/32	suspended	<a href="#">&gt;&gt; 467967</a>
62	4000	4300	black		ø1200/32	suspended	<a href="#">&gt;&gt; 467929</a>
62	3000	5060	white	yes	ø1200/32	suspended	<a href="#">&gt;&gt; 467998</a>
62	3000	5060	white		ø1200/32	suspended	<a href="#">&gt;&gt; 467950</a>
62	4000	5620	white	yes	ø1200/32	suspended	<a href="#">&gt;&gt; 467981</a>
62	4000	5620	white		ø1200/32	suspended	<a href="#">&gt;&gt; 467943</a>
62		3900	black		ø1200/32	suspended	<a href="#">&gt;&gt; 467370</a>

Card creation date: 03 October 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 217/2023; 218/2023; 34/2022