

TIUNNE PLUS

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP65; IP65/IP20
Rated power of the luminaire [W]*:	8.00 - 36.00
Luminous flux [lm]*:	590 - 3500
Colour temperature [K]:	3000; 4000
Colour rendering index:	>80; >90
Energy efficiency class:	D; E; F; G
Material of the body:	aluminium
Colour of the body:	white
Diffuser material:	PC
Diffuser type:	transparent
Mounting version:	recessed
Dimensions (H/W/T/S) [mm]:	215/215/110; 170/170/98; 96/96/73

CHARACTERISTICS

Tiunne Plus is a decorative downlight luminaire for installation in suspended ceilings. It is energy-efficient and durable thanks to the COB LED light source used. It has a classic circular shape that blends in with any type of space. It is available in several versions with different light distribution angles and four reflector colours.

The lamp housing designed in aluminium ensures optimum working conditions for the LEDs, and the aluminium reflector guarantees high luminous efficiency and low glare - features that distinguish the best LED downlight luminaires. The luminaire is suitable for installation in plasterboard and modular ceilings. Colour temperature 3000K, 4000K; CRI>80, CRI>90.

APPLICATION

The luminaire is designed for indoor use as general lighting. It is ideal for walkways, entrance areas, shop windows and fitting rooms in commercial premises.

TIUNNE PLUS

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

Tiunne Plus 1

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Colour rendering index	Beam angle [°]	Optics	Ring colour	Dimensions (H/W/T/S) [mm]	DIMM DALI	Index
8	4000	760	>80	60	reflector S	white	96/96/73		>> 416002
8	4000	760	>80	60	reflector S	black	96/96/73		>> 416057
8	4000	730	>80	20	reflector S	white	96/96/73		>> 416101
8	4000	730	>80	20	reflector S	black	96/96/73		>> 416156
8	3000	720	>80	60	reflector S	white	96/96/73		>> 416200
8	3000	720	>80	60	reflector S	black	96/96/73		>> 416255
8	3000	700	>80	20	reflector S	white	96/96/73		>> 416309
8	3000	700	>80	20	reflector S	black	96/96/73		>> 416354
8	3000	610	>90	60	reflector S	white	96/96/73		>> 416408
8	3000	610	>90	60	reflector S	black	96/96/73		>> 416453
8	3000	590	>90	20	reflector S	white	96/96/73		>> 416507
8	3000	590	>90	20	reflector S	black	96/96/73		>> 416552
8	4000	640	>90	60	reflector S	white	96/96/73		>> 416606
8	4000	640	>90	60	reflector S	black	96/96/73		>> 416651
8	4000	610	>90	20	reflector S	white	96/96/73		>> 416705
8	4000	610	>90	20	reflector S	black	96/96/73		>> 416750
8	3000	590	>90	15	reflector GS	white	96/96/73		>> 429507
8	3000	590	>90	15	reflector W	white	96/96/73		>> 430053
8	3000	590	>90	15	reflector B	black	96/96/73		>> 430459
8	3000	590	>90	15	reflector GS	black	96/96/73		>> 429552
8	3000	610	>90	60	reflector GS	white	96/96/73		>> 429408

TIUNNE PLUS

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Colour rendering index	Beam angle [°]	Optics	Ring colour	Dimensions (H/W/T/S) [mm]	DIMM DALI	Index
8	3000	610	>90	60	reflector W	white	96/96/73		>> 430008
8	3000	610	>90	60	reflector B	black	96/96/73		>> 430404
8	3000	610	>90	60	reflector GS	black	96/96/73		>> 429453
8	4000	610	>90	15	reflector GS	white	96/96/73		>> 429705
8	4000	610	>90	15	reflector W	white	96/96/73		>> 430152
8	4000	610	>90	15	reflector B	black	96/96/73		>> 430558
8	4000	610	>90	15	reflector GS	black	96/96/73		>> 429750
8	4000	640	>90	60	reflector GS	white	96/96/73		>> 429606
8	4000	640	>90	60	reflector W	white	96/96/73		>> 430107
8	4000	640	>90	60	reflector B	black	96/96/73		>> 430503
8	4000	640	>90	60	reflector GS	black	96/96/73		>> 429651
8	3000	700	>80	15	reflector GS	white	96/96/73		>> 429309
8	3000	700	>80	15	reflector W	white	96/96/73		>> 429958
8	3000	700	>80	15	reflector B	black	96/96/73		>> 430350
8	3000	700	>80	15	reflector GS	black	96/96/73		>> 429354
8	3000	720	>80	60	reflector GS	white	96/96/73		>> 429200
8	3000	720	>80	60	reflector W	white	96/96/73		>> 429903
8	3000	720	>80	60	reflector B	black	96/96/73		>> 430305
8	3000	720	>80	60	reflector GS	black	96/96/73		>> 429255
8	4000	730	>80	15	reflector GS	white	96/96/73		>> 429101
8	4000	730	>80	15	reflector W	white	96/96/73		>> 429859
8	4000	730	>80	15	reflector B	black	96/96/73		>> 430251
8	4000	730	>80	15	reflector GS	black	96/96/73		>> 429156
8	4000	760	>80	60	reflector GS	white	96/96/73		>> 429002
8	4000	760	>80	60	reflector W	white	96/96/73		>> 429804

TIUNNE PLUS

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Colour rendering index	Beam angle [°]	Optics	Ring colour	Dimensions (H/W/T/S) [mm]	DIMM DALI	Index
8	4000	760	>80	60	reflector B	black	96/96/73		>> 430206
8	4000	760	>80	60	reflector GS	black	96/96/73		>> 429057
10	4000	930	>80	60	reflector S	white	96/96/73		>> 416019
10	4000	930	>80	60	reflector S	black	96/96/73		>> 416064
10	4000	870	>80	20	reflector S	white	96/96/73		>> 416118
10	4000	870	>80	20	reflector S	black	96/96/73		>> 416163
10	3000	890	>80	60	reflector S	white	96/96/73		>> 416217
10	3000	890	>80	60	reflector S	black	96/96/73		>> 416262
10	3000	830	>80	20	reflector S	white	96/96/73		>> 416316
10	3000	830	>80	20	reflector S	black	96/96/73		>> 416361
10	3000	750	>90	60	reflector S	white	96/96/73		>> 416415
10	3000	600	>90	60	reflector S	black	96/96/73		>> 416460
10	3000	700	>90	20	reflector S	white	96/96/73		>> 416514
10	3000	700	>90	20	reflector S	black	96/96/73		>> 416569
10	4000	790	>90	60	reflector S	white	96/96/73		>> 416613
10	4000	790	>90	60	reflector S	black	96/96/73		>> 416668
10	4000	730	>90	20	reflector S	white	96/96/73		>> 416712
10	4000	730	>90	20	reflector S	black	96/96/73		>> 416767
10	3000	700	>90	15	reflector GS	white	96/96/73		>> 429514
10	3000	700	>90	15	reflector W	white	96/96/73		>> 430060
10	3000	700	>90	15	reflector B	black	96/96/73		>> 430466
10	3000	700	>90	15	reflector GS	black	96/96/73		>> 429569
10	4000	730	>90	15	reflector GS	white	96/96/73		>> 429712
10	4000	730	>90	15	reflector W	white	96/96/73		>> 430169
10	4000	730	>90	15	reflector B	black	96/96/73		>> 430565

TIUNNE PLUS

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Colour rendering index	Beam angle [°]	Optics	Ring colour	Dimensions (H/W/T/S) [mm]	DIMM DALI	Index
10	4000	730	>90	15	reflector GS	black	96/96/73		>> 429767
10	3000	750	>90	60	reflector GS	white	96/96/73		>> 429415
10	3000	750	>90	60	reflector W	white	96/96/73		>> 430015
10	3000	750	>90	60	reflector B	black	96/96/73		>> 430411
10	3000	750	>90	60	reflector GS	black	96/96/73		>> 429460
10	4000	790	>90	60	reflector GS	white	96/96/73		>> 429613
10	4000	790	>90	60	reflector W	white	96/96/73		>> 430114
10	4000	790	>90	60	reflector B	black	96/96/73		>> 430510
10	4000	790	>90	60	reflector GS	black	96/96/73		>> 429668
10	3000	830	>80	15	reflector GS	white	96/96/73		>> 429316
10	3000	830	>80	15	reflector W	white	96/96/73		>> 429965
10	3000	830	>80	15	reflector B	black	96/96/73		>> 430367
10	3000	830	>80	15	reflector GS	black	96/96/73		>> 429361
10	4000	870	>80	15	reflector GS	white	96/96/73		>> 429118
10	4000	870	>80	15	reflector W	white	96/96/73		>> 429866
10	4000	870	>80	15	reflector B	black	96/96/73		>> 430268
10	4000	870	>80	15	reflector GS	black	96/96/73		>> 429163
10	3000	890	>80	60	reflector GS	white	96/96/73		>> 429217
10	3000	730	>80	60	reflector W	white	96/96/73		>> 429910
10	3000	890	>80	60	reflector B	black	96/96/73		>> 430312
10	3000	890	>80	60	reflector GS	black	96/96/73		>> 429262
10	4000	930	>80	60	reflector GS	white	96/96/73		>> 429019
10	4000	930	>80	60	reflector W	white	96/96/73		>> 429811
10	4000	930	>80	60	reflector B	black	96/96/73		>> 430213
10	4000	930	>80	60	reflector GS	black	96/96/73		>> 429064

TIUNNE PLUS

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Colour rendering index	Beam angle [°]	Optics	Ring colour	Dimensions (H/W/T/S) [mm]	DIMM DALI	Index
14	4000	1260	>80	60	reflector S	white	96/96/73		>> 416026
14	4000	1260	>80	60	reflector S	black	96/96/73		>> 416071
14	4000	1180	>80	20	reflector S	white	96/96/73		>> 416125
14	4000	1180	>80	20	reflector S	black	96/96/73		>> 416170
14	3000	1200	>80	60	reflector S	white	96/96/73		>> 416224
14	3000	1200	>80	60	reflector S	black	96/96/73		>> 416279
14	3000	1120	>80	20	reflector S	white	96/96/73		>> 416323
14	3000	1120	>80	20	reflector S	black	96/96/73		>> 416378
14	3000	1020	>90	60	reflector S	white	96/96/73		>> 416422
14	3000	1020	>90	60	reflector S	black	96/96/73		>> 416477
14	3000	950	>90	20	reflector S	white	96/96/73		>> 416521
14	3000	950	>90	20	reflector S	black	96/96/73		>> 416576
14	4000	1060	>90	60	reflector S	white	96/96/73		>> 416620
14	4000	1060	>90	60	reflector S	black	96/96/73		>> 416675
14	4000	990	>90	20	reflector S	white	96/96/73		>> 416729
14	4000	990	>90	20	reflector S	black	96/96/73		>> 416774
14	3000	1020	>90	60	reflector GS	white	96/96/73		>> 429422
14	3000	1020	>90	60	reflector W	white	96/96/73		>> 430022
14	3000	1020	>90	60	reflector B	black	96/96/73		>> 430428
14	3000	1020	>90	60	reflector GS	black	96/96/73		>> 429477
14	4000	1060	>90	60	reflector GS	white	96/96/73		>> 429620
14	4000	1060	>90	60	reflector W	white	96/96/73		>> 430121
14	4000	1060	>90	60	reflector B	black	96/96/73		>> 430527
14	4000	1060	>90	60	reflector GS	black	96/96/73		>> 429675
14	3000	1120	>80	15	reflector GS	white	96/96/73		>> 429323

TIUNNE PLUS

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Colour rendering index	Beam angle [°]	Optics	Ring colour	Dimensions (H/W/T/S) [mm]	DIMM DALI	Index
14	3000	1120	>80	15	reflector W	white	96/96/73		>> 429972
14	3000	1120	>80	15	reflector B	black	96/96/73		>> 430374
14	3000	1120	>80	15	reflector GS	black	96/96/73		>> 429378
14	4000	1180	>80	15	reflector GS	white	96/96/73		>> 429125
14	4000	1180	>80	15	reflector W	white	96/96/73		>> 429873
14	4000	1180	>80	15	reflector B	black	96/96/73		>> 430275
14	4000	1180	>80	15	reflector GS	black	96/96/73		>> 429170
14	3000	1200	>80	60	reflector GS	white	96/96/73		>> 429224
14	3000	1200	>80	60	reflector W	white	96/96/73		>> 429927
14	3000	1200	>80	60	reflector B	black	96/96/73		>> 430329
14	3000	1200	>80	60	reflector GS	black	96/96/73		>> 429279
14	4000	1260	>80	60	reflector GS	white	96/96/73		>> 429026
14	4000	1260	>80	60	reflector W	white	96/96/73		>> 429828
14	4000	1260	>80	60	reflector B	black	96/96/73		>> 430220
14	4000	1260	>80	60	reflector GS	black	96/96/73		>> 429071
14	3000	950	>90	15	reflector GS	white	96/96/73		>> 429521
14	3000	950	>90	15	reflector W	white	96/96/73		>> 430077
14	3000	950	>90	15	reflector B	black	96/96/73		>> 430473
14	3000	950	>90	15	reflector GS	black	96/96/73		>> 429576
14	4000	990	>90	15	reflector GS	white	96/96/73		>> 429729
14	4000	990	>90	15	reflector W	white	96/96/73		>> 430176
14	4000	990	>90	15	reflector B	black	96/96/73		>> 430572
14	4000	990	>90	15	reflector GS	black	96/96/73		>> 429774
16	4000	1360	>80	60	reflector S	white	96/96/73		>> 416033
16	4000	1360	>80	60	reflector S	white	96/96/73	yes	>> 416040

TIUNNE PLUS

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Colour rendering index	Beam angle [°]	Optics	Ring colour	Dimensions (H/W/T/S) [mm]	DIMM DALI	Index
16	4000	1360	>80	60	reflector S	black	96/96/73		>> 416088
16	4000	1360	>80	60	reflector S	black	96/96/73	yes	>> 416095
16	4000	1270	>80	20	reflector S	white	96/96/73		>> 416132
16	4000	1270	>80	20	reflector S	white	96/96/73	yes	>> 416149
16	4000	1270	>80	20	reflector S	black	96/96/73		>> 416187
16	4000	1270	>80	20	reflector S	black	96/96/73	yes	>> 416194
16	3000	1300	>80	60	reflector S	white	96/96/73		>> 416231
16	3000	1300	>80	60	reflector S	white	96/96/73	yes	>> 416248
16	3000	1300	>80	60	reflector S	black	96/96/73		>> 416286
16	3000	1300	>80	60	reflector S	black	96/96/73	yes	>> 416293
16	3000	1210	>80	20	reflector S	white	96/96/73		>> 416330
16	3000	1210	>80	20	reflector S	white	96/96/73	yes	>> 416347
16	3000	1210	>80	20	reflector S	black	96/96/73		>> 416385
16	3000	1210	>80	20	reflector S	black	96/96/73	yes	>> 416392
16	3000	1100	>90	60	reflector S	white	96/96/73		>> 416439
16	3000	1100	>90	60	reflector S	white	96/96/73	yes	>> 416446
16	3000	1100	>90	60	reflector S	black	96/96/73		>> 416484
16	3000	1100	>90	60	reflector S	black	96/96/73	yes	>> 416491
16	3000	1020	>90	60	reflector S	white	96/96/73		>> 416538
16	3000	1020	>90	20	reflector S	white	96/96/73	yes	>> 416545
16	3000	1020	>90	20	reflector S	black	96/96/73		>> 416583
16	3000	1020	>90	20	reflector S	black	96/96/73	yes	>> 416590
16	4000	1140	>90	60	reflector S	white	96/96/73		>> 416637
16	4000	1140	>90	60	reflector S	white	96/96/73	yes	>> 416644
16	4000	1140	>90	60	reflector S	black	96/96/73		>> 416682

TIUNNE PLUS

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Colour rendering index	Beam angle [°]	Optics	Ring colour	Dimensions (H/W/T/S) [mm]	DIMM DALI	Index
16	4000	1140	>90	60	reflector S	black	96/96/73	yes	>> 416699
16	4000	1070	>90	20	reflector S	white	96/96/73		>> 416736
16	4000	1070	>90	20	reflector S	white	96/96/73	yes	>> 416743
16	4000	1070	>90	20	reflector S	black	96/96/73		>> 416781
16	4000	1070	>90	20	reflector S	black	96/96/73	yes	>> 416798
16	3000	1020	>90	15	reflector GS	white	96/96/73		>> 429538
16	3000	1020	>90	15	reflector W	white	96/96/73		>> 430084
16	3000	1020	>90	15	reflector B	black	96/96/73		>> 430480
16	3000	1020	>90	15	reflector GS	black	96/96/73		>> 429583
16	3000	1020	>90	15	reflector GS	white	96/96/73		>> 429545
16	3000	1020	>90	15	reflector W	white	96/96/73		>> 430091
16	3000	1020	>90	15	reflector B	black	96/96/73		>> 430497
16	3000	1020	>90	15	reflector GS	black	96/96/73		>> 429590
16	4000	1070	>90	15	reflector GS	white	96/96/73		>> 429736
16	4000	1070	>90	15	reflector W	white	96/96/73		>> 430183
16	4000	1070	>90	15	reflector B	black	96/96/73		>> 430589
16	4000	1070	>90	15	reflector GS	black	96/96/73		>> 429781
16	4000	1070	>90	15	reflector GS	white	96/96/73		>> 429743
16	4000	1070	>90	15	reflector W	white	96/96/73		>> 430190
16	4000	1070	>90	15	reflector B	black	96/96/73		>> 430596
16	4000	1070	>90	15	reflector GS	black	96/96/73		>> 429798
16	3000	1100	>90	60	reflector GS	white	96/96/73		>> 429439
16	3000	1100	>90	60	reflector W	white	96/96/73		>> 430039
16	3000	1100	>90	60	reflector B	black	96/96/73		>> 430435
16	3000	1100	>90	60	reflector GS	black	96/96/73		>> 429484

TIUNNE PLUS

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Colour rendering index	Beam angle [°]	Optics	Ring colour	Dimensions (H/W/T/S) [mm]	DIMM DALI	Index
16	3000	1100	>90	60	reflector GS	white	96/96/73		>> 429446
16	3000	1100	>90	60	reflector W	white	96/96/73		>> 430046
16	3000	1100	>90	60	reflector B	black	96/96/73		>> 430442
16	3000	1100	>90	60	reflector GS	black	96/96/73		>> 429491
16	4000	1140	>90	60	reflector GS	white	96/96/73		>> 429637
16	4000	1140	>90	60	reflector W	white	96/96/73		>> 430138
16	4000	1140	>90	60	reflector B	black	96/96/73		>> 430534
16	4000	1140	>90	60	reflector GS	black	96/96/73		>> 429682
16	4000	1140	>90	60	reflector GS	white	96/96/73		>> 429644
16	4000	1140	>90	60	reflector W	white	96/96/73		>> 430145
16	4000	1140	>90	60	reflector B	black	96/96/73		>> 430541
16	4000	1140	>90	60	reflector GS	black	96/96/73		>> 429699
16	3000	1210	>80	15	reflector GS	white	96/96/73		>> 429330
16	3000	1210	>80	15	reflector W	white	96/96/73		>> 429989
16	3000	1210	>80	15	reflector B	black	96/96/73		>> 430381
16	3000	1210	>80	15	reflector GS	black	96/96/73		>> 429385
16	3000	1210	>80	15	reflector GS	white	96/96/73		>> 429347
16	3000	1210	>80	15	reflector W	white	96/96/73		>> 429996
16	3000	1210	>80	15	reflector B	black	96/96/73		>> 430398
16	3000	1210	>80	15	reflector GS	black	96/96/73		>> 429392
16	4000	1270	>80	15	reflector GS	white	96/96/73		>> 429132
16	4000	1270	>80	15	reflector W	white	96/96/73		>> 429880
16	4000	1270	>80	15	reflector B	black	96/96/73		>> 430282
16	4000	1270	>80	15	reflector GS	black	96/96/73		>> 429187
16	4000	1270	>80	15	reflector GS	white	96/96/73		>> 429149

TIUNNE PLUS

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Colour rendering index	Beam angle [°]	Optics	Ring colour	Dimensions (H/W/T/S) [mm]	DIMM DALI	Index
16	4000	1270	>80	15	reflector W	white	96/96/73		>> 429897
16	4000	1270	>80	15	reflector B	black	96/96/73		>> 430299
16	4000	1270	>80	15	reflector GS	black	96/96/73		>> 429194
16	3000	1300	>80	60	reflector GS	white	96/96/73		>> 429231
16	3000	1300	>80	60	reflector W	white	96/96/73		>> 429934
16	3000	1300	>80	60	reflector B	black	96/96/73		>> 430336
16	3000	1300	>80	60	reflector GS	black	96/96/73		>> 429286
16	3000	1300	>80	60	reflector GS	white	96/96/73		>> 429248
16	3000	1300	>80	60	reflector W	white	96/96/73		>> 429941
16	3000	1300	>80	60	reflector B	black	96/96/73		>> 430343
16	3000	1300	>80	60	reflector GS	black	96/96/73		>> 429293
16	4000	1360	>80	60	reflector GS	white	96/96/73		>> 429033
16	4000	1360	>80	60	reflector W	white	96/96/73		>> 429835
16	4000	1360	>80	60	reflector B	black	96/96/73		>> 430237
16	4000	1360	>80	60	reflector GS	black	96/96/73		>> 429088
16	4000	1360	>80	60	reflector GS	white	96/96/73		>> 429040
16	4000	1360	>80	60	reflector W	white	96/96/73		>> 429842
16	4000	1360	>80	60	reflector B	black	96/96/73		>> 430244
16	4000	1360	>80	60	reflector GS	black	96/96/73		>> 429095

Tiunne Plus 2

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Colour rendering index	Beam angle [°]	Optics	Ring colour	Dimensions (H/W/T/S) [mm]	DIMM DALI	Index
8	3000	720	>90	15	reflector	white	170/170/98		>> 417405
8	3000	700	>90	15	reflector	black	170/170/98		>> 417443
8	3000	820	>90	60	reflector	white	170/170/98		>> 417320
8	3000	720	>90	60	reflector	black	170/170/98		>> 417368
8	4000	740	>90	15	reflector	white	170/170/98		>> 417566
8	4000	730	>90	15	reflector	black	170/170/98		>> 417603

TIUNNE PLUS

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Colour rendering index	Beam angle [°]	Optics	Ring colour	Dimensions (H/W/T/S) [mm]	DIMM DALI	Index
8	4000	700	>90	60	reflector	white	170/170/98		>> 417481
8	4000	740	>90	60	reflector	black	170/170/98		>> 417528
8	3000	840	>80	15	reflector	white	170/170/98		>> 417245
8	3000	820	>80	15	reflector	black	170/170/98		>> 417283
8	3000	870	>80	60	reflector	white	170/170/98		>> 417160
8	3000	840	>80	60	reflector	black	170/170/98		>> 417207
8	4000	890	>80	15	reflector	white	170/170/98		>> 417085
8	4000	870	>80	15	reflector	black	170/170/98		>> 417122
8	4000	890	>80	60	reflector	white	170/170/98		>> 417009
8	4000	890	>80	60	reflector	black	170/170/98		>> 417047
8	3000	700	>90	15	reflector GS	white	170/170/98		>> 431807
8	3000	700	>90	15	reflector W	white	170/170/98		>> 430800
8	3000	700	>90	15	reflector B	black	170/170/98		>> 431203
8	3000	700	>90	15	reflector GS	black	170/170/98		>> 431845
8	3000	720	>90	60	reflector GS	white	170/170/98		>> 431722
8	3000	720	>90	60	reflector W	white	170/170/98		>> 430763
8	3000	720	>90	60	reflector B	black	170/170/98		>> 431166
8	3000	720	>90	60	reflector GS	black	170/170/98		>> 431760
8	4000	730	>90	15	reflector GS	white	170/170/98		>> 431968
8	4000	730	>90	15	reflector W	white	170/170/98		>> 430886
8	4000	730	>90	15	reflector B	black	170/170/98		>> 431289
8	4000	730	>90	15	reflector GS	black	170/170/98		>> 432002
8	4000	740	>90	60	reflector GS	white	170/170/98		>> 431883
8	4000	740	>90	60	reflector W	white	170/170/98		>> 430848
8	4000	740	>90	60	reflector B	black	170/170/98		>> 431241
8	4000	740	>90	60	reflector GS	black	170/170/98		>> 431920
8	3000	820	>80	15	reflector GS	white	170/170/98		>> 431647
8	3000	820	>80	15	reflector W	white	170/170/98		>> 430725

TIUNNE PLUS

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Colour rendering index	Beam angle [°]	Optics	Ring colour	Dimensions (H/W/T/S) [mm]	DIMM DALI	Index
8	3000	820	>80	15	reflector B	black	170/170/98		>> 431128
8	3000	820	>80	15	reflector GS	black	170/170/98		>> 431685
8	3000	840	>80	60	reflector GS	white	170/170/98		>> 431562
8	3000	840	>80	60	reflector W	white	170/170/98		>> 430688
8	3000	840	>80	60	reflector B	black	170/170/98		>> 431081
8	3000	840	>80	60	reflector GS	black	170/170/98		>> 431609
8	4000	870	>80	15	reflector GS	white	170/170/98		>> 431487
8	4000	870	>80	15	reflector W	white	170/170/98		>> 430640
8	4000	870	>80	15	reflector B	black	170/170/98		>> 431043
8	4000	870	>80	15	reflector GS	black	170/170/98		>> 431524
8	4000	890	>80	60	reflector GS	white	170/170/98		>> 431401
8	4000	890	>80	60	reflector W	white	170/170/98		>> 430602
8	4000	890	>80	60	reflector B	black	170/170/98		>> 431005
8	4000	890	>80	60	reflector GS	black	170/170/98		>> 431449
12	3000	1070	>90	15	reflector	white	170/170/98		>> 417412
12	3000	1060	>90	15	reflector	black	170/170/98		>> 417450
12	3000	1240	>90	60	reflector	white	170/170/98		>> 417337
12	3000	1070	>90	60	reflector	black	170/170/98		>> 417375
12	4000	1000	>90	15	reflector	white	170/170/98		>> 417573
12	4000	1090	>90	15	reflector	black	170/170/98		>> 417610
12	4000	1060	>90	60	reflector	white	170/170/98		>> 417498
12	4000	1100	>90	60	reflector	black	170/170/98		>> 417535
12	3000	1250	>80	15	reflector	white	170/170/98		>> 417252
12	3000	1240	>80	15	reflector	black	170/170/98		>> 417290
12	3000	1310	>80	60	reflector	white	170/170/98		>> 417177
12	3000	1250	>80	60	reflector	black	170/170/98		>> 417214
12	4000	1320	>80	15	reflector	white	170/170/98		>> 417092
12	4000	1310	>80	15	reflector	black	170/170/98		>> 417139
12	4000	1320	>80	60	reflector	white	170/170/98		>> 417016
12	4000	1320	>80	60	reflector	black	170/170/98		>> 417054

TIUNNE PLUS

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Colour rendering index	Beam angle [°]	Optics	Ring colour	Dimensions (H/W/T/S) [mm]	DIMM DALI	Index
12	3000	1060	>90	15	reflector GS	white	170/170/98		>> 431814
12	3000	1060	>90	15	reflector W	white	170/170/98		>> 430817
12	3000	1060	>90	15	reflector B	black	170/170/98		>> 431210
12	3000	1060	>90	15	reflector GS	black	170/170/98		>> 431852
12	3000	1070	>90	60	reflector GS	white	170/170/98		>> 431739
12	3000	1070	>90	60	reflector W	white	170/170/98		>> 430770
12	3000	1070	>90	60	reflector B	black	170/170/98		>> 431173
12	3000	1070	>90	60	reflector GS	black	170/170/98		>> 431777
12	4000	1090	>90	15	reflector GS	white	170/170/98		>> 431975
12	4000	1090	>90	15	reflector W	white	170/170/98		>> 430893
12	4000	1090	>90	15	reflector B	black	170/170/98		>> 431296
12	4000	1090	>90	15	reflector GS	black	170/170/98		>> 432019
12	4000	1100	>90	60	reflector GS	white	170/170/98		>> 431890
12	4000	1100	>90	60	reflector W	white	170/170/98		>> 430855
12	4000	1100	>90	60	reflector B	black	170/170/98		>> 431258
12	4000	1100	>90	60	reflector GS	black	170/170/98		>> 431937
12	3000	1240	>80	15	reflector GS	white	170/170/98		>> 431654
12	3000	1240	>80	15	reflector W	white	170/170/98		>> 430732
12	3000	1240	>80	15	reflector B	black	170/170/98		>> 431135
12	3000	1240	>80	15	reflector GS	black	170/170/98		>> 431692
12	3000	1250	>80	60	reflector GS	white	170/170/98		>> 431579
12	3000	1250	>80	60	reflector W	white	170/170/98		>> 430695
12	3000	1250	>80	60	reflector B	black	170/170/98		>> 431098
12	3000	1250	>80	60	reflector GS	black	170/170/98		>> 431616
12	4000	1310	>80	15	reflector GS	white	170/170/98		>> 431494

TIUNNE PLUS

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Colour rendering index	Beam angle [°]	Optics	Ring colour	Dimensions (H/W/T/S) [mm]	DIMM DALI	Index
12	4000	1310	>80	15	reflector W	white	170/170/98		>> 430657
12	4000	1310	>80	15	reflector B	black	170/170/98		>> 431050
12	4000	1310	>80	15	reflector GS	black	170/170/98		>> 431531
12	4000	1320	>80	60	reflector GS	white	170/170/98		>> 431418
12	4000	1320	>80	60	reflector W	white	170/170/98		>> 430619
12	4000	1320	>80	60	reflector B	black	170/170/98		>> 431012
12	4000	1320	>80	60	reflector GS	black	170/170/98		>> 431456
23	3000	2400	>80	15	reflector	white	170/170/98		>> 417269
23	3000	2350	>80	15	reflector	black	170/170/98		>> 417306
23	3000	2000	>90	15	reflector	white	170/170/98		>> 417429
23	3000	1950	>90	15	reflector	black	170/170/98		>> 417467
23	3000	2350	>90	60	reflector	white	170/170/98		>> 417344
23	3000	2000	>90	60	reflector	black	170/170/98		>> 417382
23	4000	2200	>90	15	reflector	white	170/170/98		>> 417580
23	4000	2150	>90	15	reflector	black	170/170/98		>> 417627
23	4000	1950	>90	60	reflector	white	170/170/98		>> 417504
23	4000	2200	>90	60	reflector	black	170/170/98		>> 417542
23	3000	2450	>80	60	reflector	white	170/170/98		>> 417184
23	3000	2400	>80	60	reflector	black	170/170/98		>> 417221
23	4000	2500	>80	15	reflector	white	170/170/98		>> 417108
23	4000	2450	>80	15	reflector	black	170/170/98		>> 417146
23	4000	2500	>80	60	reflector	white	170/170/98		>> 417023
23	4000	2500	>80	60	reflector	black	170/170/98		>> 417061
23	3000	1950	>90	15	reflector GS	white	170/170/98		>> 431821
23	3000	1950	>90	15	reflector W	white	170/170/98		>> 430824
23	3000	1950	>90	15	reflector B	black	170/170/98		>> 431227
23	3000	1950	>90	15	reflector GS	black	170/170/98		>> 431869
23	3000	2000	>90	60	reflector GS	white	170/170/98		>> 431746
23	3000	2000	>90	60	reflector W	white	170/170/98		>> 430787
23	3000	2000	>90	60	reflector B	black	170/170/98		>> 431180

TIUNNE PLUS

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Colour rendering index	Beam angle [°]	Optics	Ring colour	Dimensions (H/W/T/S) [mm]	DIMM DALI	Index
23	3000	2000	>90	60	reflector GS	black	170/170/98		>> 431784
23	4000	2150	>90	15	reflector GS	white	170/170/98		>> 431982
23	4000	2150	>90	15	reflector W	white	170/170/98		>> 430909
23	4000	2150	>90	15	reflector B	black	170/170/98		>> 431302
23	4000	2150	>90	15	reflector GS	black	170/170/98		>> 432026
23	4000	2200	>90	60	reflector GS	white	170/170/98		>> 431906
23	4000	2200	>90	60	reflector W	white	170/170/98		>> 430862
23	4000	2200	>90	60	reflector B	black	170/170/98		>> 431265
23	4000	2200	>90	60	reflector GS	black	170/170/98		>> 431944
23	3000	2350	>80	15	reflector GS	white	170/170/98		>> 431661
23	3000	2350	>80	15	reflector W	white	170/170/98		>> 430749
23	3000	2350	>80	15	reflector B	black	170/170/98		>> 431142
23	3000	2350	>80	15	reflector GS	black	170/170/98		>> 431708
23	3000	2400	>80	60	reflector GS	white	170/170/98		>> 431586
23	3000	2400	>80	60	reflector W	white	170/170/98		>> 430701
23	3000	2400	>80	60	reflector B	black	170/170/98		>> 431104
23	3000	2400	>80	60	reflector GS	black	170/170/98		>> 431623
23	4000	2450	>80	15	reflector GS	white	170/170/98		>> 431500
23	4000	2450	>80	15	reflector W	white	170/170/98		>> 430664
23	4000	2450	>80	15	reflector B	black	170/170/98		>> 431067
23	4000	2450	>80	15	reflector GS	black	170/170/98		>> 431548
23	4000	2500	>80	60	reflector GS	white	170/170/98		>> 431425
23	4000	2500	>80	60	reflector W	white	170/170/98		>> 430626
23	4000	2500	>80	60	reflector B	black	170/170/98		>> 431029
23	4000	2500	>80	60	reflector GS	black	170/170/98		>> 431463

TIUNNE PLUS

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Colour rendering index	Beam angle [°]	Optics	Ring colour	Dimensions (H/W/T/S) [mm]	DIMM DALI	Index
31	3000	3000	>80	15	reflector	white	170/170/98		>> 417276
31	3000	2950	>80	15	reflector	black	170/170/98		>> 417313
31	3000	1240	>80	20	reflector	white	170/170/98	yes	>> 417702
31	3000	1240	>80	20	reflector	black	170/170/98	yes	>> 417719
31	3000	2500	>90	15	reflector	white	170/170/98		>> 417436
31	3000	2450	>90	15	reflector	black	170/170/98		>> 417474
31	3000	2270	>90	20	reflector	white	170/170/98	yes	>> 417740
31	3000	2270	>90	20	reflector	black	170/170/98	yes	>> 417757
31	4000	2700	>90	15	reflector	white	170/170/98		>> 417597
31	4000	2650	>90	15	reflector	black	170/170/98		>> 417634
31	4000	2330	>90	20	reflector	white	170/170/98	yes	>> 417788
31	4000	2330	>90	20	reflector	black	170/170/98	yes	>> 417795
31	3000	2950	>90	60	reflector	white	170/170/98		>> 417351
31	3000	2500	>90	60	reflector	black	170/170/98		>> 417399
31	3000	2350	>90	60	reflector	white	170/170/98	yes	>> 417726
31	3000	2350	>90	60	reflector	black	170/170/98	yes	>> 417733
31	4000	2450	>90	60	reflector	white	170/170/98		>> 417511
31	4000	2700	>90	60	reflector	black	170/170/98		>> 417559
31	4000	2420	>90	60	reflector	white	170/170/98	yes	>> 417764
31	4000	2420	>90	60	reflector	black	170/170/98	yes	>> 417771
31	3000	3050	>80	60	reflector	white	170/170/98		>> 417191
31	3000	3000	>80	60	reflector	black	170/170/98		>> 417238
31	3000	2740	>80	60	reflector	white	170/170/98	yes	>> 417689
31	3000	2740	>80	60	reflector	black	170/170/98	yes	>> 417696
31	4000	3100	>80	15	reflector	white	170/170/98		>> 417115
31	4000	3050	>80	15	reflector	black	170/170/98		>> 417153
31	4000	2800	>80	20	reflector	white	170/170/98	yes	>> 417665
31	4000	2800	>80	20	reflector	black	170/170/98	yes	>> 417672
31	4000	3100	>80	60	reflector	white	170/170/98		>> 417030
31	4000	3100	>80	60	reflector	black	170/170/98		>> 417078
31	4000	2900	>80	60	reflector	white	170/170/98	yes	>> 417641
31	4000	2900	>80	60	reflector	black	170/170/98	yes	>> 417658
31	3000	2450	>90	15	reflector GS	white	170/170/98		>> 431838
31	3000	2450	>90	15	reflector W	white	170/170/98		>> 430831
31	3000	2450	>90	15	reflector B	black	170/170/98		>> 431234
31	3000	2450	>90	15	reflector GS	black	170/170/98		>> 431876

TIUNNE PLUS

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Colour rendering index	Beam angle [°]	Optics	Ring colour	Dimensions (H/W/T/S) [mm]	DIMM DALI	Index
31	3000	2450	>90	15	reflector GS	white	170/170/98		>> 432149
31	3000	2450	>90	15	reflector W	white	170/170/98		>> 430978
31	3000	2450	>90	15	reflector B	black	170/170/98		>> 431371
31	3000	2450	>90	15	reflector GS	black	170/170/98		>> 432156
31	3000	2500	>90	60	reflector GS	white	170/170/98		>> 431753
31	3000	2500	>90	60	reflector W	white	170/170/98		>> 430794
31	3000	2500	>90	60	reflector B	black	170/170/98		>> 431197
31	3000	2500	>90	60	reflector GS	black	170/170/98		>> 431791
31	3000	2500	>90	60	reflector GS	white	170/170/98		>> 432125
31	3000	2500	>90	60	reflector W	white	170/170/98		>> 430961
31	3000	2500	>90	60	reflector B	black	170/170/98		>> 431364
31	3000	2500	>90	60	reflector GS	black	170/170/98		>> 432132
31	4000	2650	>90	15	reflector GS	white	170/170/98		>> 431999
31	4000	2650	>90	15	reflector W	white	170/170/98		>> 430916
31	4000	2650	>90	15	reflector B	black	170/170/98		>> 431319
31	4000	2650	>90	15	reflector GS	black	170/170/98		>> 432033
31	4000	2650	>90	15	reflector GS	white	170/170/98		>> 432187
31	4000	2650	>90	15	reflector W	white	170/170/98		>> 430992
31	4000	2650	>90	15	reflector B	black	170/170/98		>> 431395
31	4000	2650	>90	15	reflector GS	black	170/170/98		>> 432194
31	4000	2700	>90	60	reflector GS	white	170/170/98		>> 431913
31	4000	2700	>90	60	reflector W	white	170/170/98		>> 430879
31	4000	2700	>90	60	reflector B	black	170/170/98		>> 431272
31	4000	2700	>90	60	reflector GS	black	170/170/98		>> 431951
31	4000	2700	>90	60	reflector GS	white	170/170/98		>> 432163

TIUNNE PLUS

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Colour rendering index	Beam angle [°]	Optics	Ring colour	Dimensions (H/W/T/S) [mm]	DIMM DALI	Index
31	4000	2700	>90	60	reflector W	white	170/170/98		>> 430985
31	4000	2700	>90	60	reflector B	black	170/170/98		>> 431388
31	4000	2700	>90	60	reflector GS	black	170/170/98		>> 432170
31	3000	2950	>80	15	reflector GS	white	170/170/98		>> 431678
31	3000	2950	>80	15	reflector W	white	170/170/98		>> 430756
31	3000	2950	>80	15	reflector B	black	170/170/98		>> 431159
31	3000	2950	>80	15	reflector GS	black	170/170/98		>> 431715
31	3000	2950	>80	15	reflector GS	white	170/170/98		>> 432101
31	3000	2950	>80	15	reflector W	white	170/170/98		>> 430954
31	3000	2950	>80	15	reflector B	black	170/170/98		>> 431357
31	3000	2950	>80	15	reflector GS	black	170/170/98		>> 432118
31	3000	3000	>80	60	reflector GS	white	170/170/98		>> 431593
31	3000	3000	>80	60	reflector W	white	170/170/98		>> 430718
31	3000	3000	>80	60	reflector B	black	170/170/98		>> 431111
31	3000	3000	>80	60	reflector GS	black	170/170/98		>> 431630
31	3000	3000	>80	60	reflector GS	white	170/170/98		>> 432088
31	3000	3000	>80	60	reflector W	white	170/170/98		>> 430947
31	3000	3000	>80	60	reflector B	black	170/170/98		>> 431340
31	3000	3000	>80	60	reflector GS	black	170/170/98		>> 432095
31	4000	3050	>80	15	reflector GS	white	170/170/98		>> 431517
31	4000	3050	>80	15	reflector W	white	170/170/98		>> 430671
31	4000	3050	>80	15	reflector B	black	170/170/98		>> 431074
31	4000	3050	>80	15	reflector GS	black	170/170/98		>> 431555
31	4000	3050	>80	15	reflector GS	white	170/170/98		>> 432064
31	4000	3050	>80	15	reflector W	white	170/170/98		>> 430930

TIUNNE PLUS

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Colour rendering index	Beam angle [°]	Optics	Ring colour	Dimensions (H/W/T/S) [mm]	DIMM DALI	Index
31	4000	3050	>80	15	reflector B	black	170/170/98		>> 431333
31	4000	3050	>80	15	reflector GS	black	170/170/98		>> 432071
31	4000	3100	>80	60	reflector GS	white	170/170/98		>> 431432
31	4000	3100	>80	60	reflector W	white	170/170/98		>> 430633
31	4000	3100	>80	60	reflector B	black	170/170/98		>> 431036
31	4000	3100	>80	60	reflector GS	black	170/170/98		>> 431470
31	4000	3100	>80	60	reflector GS	white	170/170/98		>> 432040
31	4000	3100	>80	60	reflector W	white	170/170/98		>> 430923
31	4000	3100	>80	60	reflector B	black	170/170/98		>> 431326
31	4000	3100	>80	60	reflector GS	black	170/170/98		>> 432057

Tiunne Plus 3

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Colour rendering index	Beam angle [°]	Optics	Ring colour	Dimensions (H/W/T/S) [mm]	DIMM DALI	Index
8	3000	850	>80	15	reflector	white	215/215/110		>> 425141
8	3000	850	>80	15	reflector	black	215/215/110		>> 425219
8	3000	850	>80	15	reflector	white	215/215/110		>> 425424
8	3000	850	>80	15	reflector	black	215/215/110		>> 425493
8	3000	850	>80	15	reflector	white	215/215/110		>> 425707
8	3000	850	>80	15	reflector	black	215/215/110		>> 425776
8	4000	900	>80	15	reflector	white	215/215/110		>> 913167
8	4000	900	>80	15	reflector	black	215/215/110		>> 913235
8	4000	900	>80	15	reflector	white	215/215/110		>> 913440
8	4000	900	>80	15	reflector	black	215/215/110		>> 913518
8	4000	900	>80	15	reflector	white	215/215/110		>> 913723
8	4000	900	>80	15	reflector	black	215/215/110		>> 913792
8	4000	900	>80	15	reflector	white	215/215/110		>> 921346
8	4000	900	>80	15	reflector	black	215/215/110		>> 921414
8	3000	850	>80	15	reflector	white	215/215/110		>> 921629
8	3000	850	>80	15	reflector	black	215/215/110		>> 921698
8	3000	940	>80	60	reflector	white	215/215/110		>> 921490
8	3000	940	>80	60	reflector	white	215/215/110		>> 425295
8	3000	940	>80	60	reflector	white	215/215/110		>> 425011
8	3000	940	>80	60	reflector	white	215/215/110		>> 425578

TIUNNE PLUS

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Colour rendering index	Beam angle [°]	Optics	Ring colour	Dimensions (H/W/T/S) [mm]	DIMM DALI	Index
8	3000	940	>80	60	reflector	black	215/215/110		>> 921551
8	3000	940	>80	60	reflector	black	215/215/110		>> 425356
8	3000	940	>80	60	reflector	black	215/215/110		>> 425073
8	3000	940	>80	60	reflector	black	215/215/110		>> 425639
8	4000	960	>80	60	reflector	white	215/215/110		>> 921216
8	4000	960	>80	60	reflector	white	215/215/110		>> 913310
8	4000	960	>80	60	reflector	white	215/215/110		>> 913013
8	4000	960	>80	60	reflector	white	215/215/110		>> 913594
8	4000	960	>80	60	reflector	black	215/215/110		>> 921278
8	4000	960	>80	60	reflector	black	215/215/110		>> 913372
8	4000	960	>80	60	reflector	black	215/215/110		>> 913075
8	4000	960	>80	60	reflector	black	215/215/110		>> 913655
14	3000	1500	>80	15	reflector	white	215/215/110		>> 425158
14	3000	1500	>80	15	reflector	black	215/215/110		>> 425226
14	3000	1500	>80	15	reflector	white	215/215/110		>> 425431
14	3000	1500	>80	15	reflector	black	215/215/110		>> 425509
14	3000	1500	>80	15	reflector	white	215/215/110		>> 425714
14	3000	1500	>80	15	reflector	black	215/215/110		>> 425783
14	4000	1550	>80	15	reflector	white	215/215/110		>> 913174
14	4000	1550	>80	15	reflector	black	215/215/110		>> 913242
14	4000	1550	>80	15	reflector	white	215/215/110		>> 913457
14	4000	1550	>80	15	reflector	black	215/215/110		>> 913525
14	4000	1550	>80	15	reflector	white	215/215/110		>> 913730
14	4000	1550	>80	15	reflector	black	215/215/110		>> 913808
14	4000	1550	>80	15	reflector	white	215/215/110		>> 921353
14	4000	1550	>80	15	reflector	black	215/215/110		>> 921421
14	3000	1500	>80	15	reflector	white	215/215/110		>> 921636
14	3000	1500	>80	15	reflector	black	215/215/110		>> 921704
14	3000	1600	>80	60	reflector	white	215/215/110		>> 921506
14	3000	1600	>80	60	reflector	white	215/215/110		>> 425301
14	3000	1600	>80	60	reflector	white	215/215/110		>> 425028
14	3000	1600	>80	60	reflector	white	215/215/110		>> 425585
14	3000	1600	>80	60	reflector	black	215/215/110		>> 921568
14	3000	1600	>80	60	reflector	black	215/215/110		>> 425363
14	3000	1600	>80	60	reflector	black	215/215/110		>> 425080
14	3000	1600	>80	60	reflector	black	215/215/110		>> 425646
14	4000	1650	>80	60	reflector	white	215/215/110		>> 921223
14	4000	1650	>80	60	reflector	white	215/215/110		>> 913327

TIUNNE PLUS

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Colour rendering index	Beam angle [°]	Optics	Ring colour	Dimensions (H/W/T/S) [mm]	DIMM DALI	Index
14	4000	1650	>80	60	reflector	white	215/215/110		>> 913020
14	4000	1650	>80	60	reflector	white	215/215/110		>> 913600
14	4000	1650	>80	60	reflector	black	215/215/110		>> 921285
14	4000	1650	>80	60	reflector	black	215/215/110		>> 913389
14	4000	1650	>80	60	reflector	black	215/215/110		>> 913082
14	4000	1650	>80	60	reflector	black	215/215/110		>> 913662
20	3000	2050	>80	15	reflector	white	215/215/110		>> 425165
20	3000	2050	>80	15	reflector	black	215/215/110		>> 425233
20	3000	2050	>80	15	reflector	white	215/215/110		>> 425448
20	3000	2050	>80	15	reflector	black	215/215/110		>> 425516
20	3000	2050	>80	15	reflector	white	215/215/110		>> 425721
20	3000	2050	>80	15	reflector	black	215/215/110		>> 425790
20	4000	2100	>80	15	reflector	white	215/215/110		>> 913181
20	4000	2100	>80	15	reflector	black	215/215/110		>> 913259
20	4000	2100	>80	15	reflector	white	215/215/110		>> 913464
20	4000	2100	>80	15	reflector	black	215/215/110		>> 913532
20	4000	2100	>80	15	reflector	white	215/215/110		>> 913747
20	4000	2100	>80	15	reflector	black	215/215/110		>> 913815
20	4000	2100	>80	15	reflector	white	215/215/110		>> 921360
20	4000	2100	>80	15	reflector	black	215/215/110		>> 921438
20	3000	2050	>80	15	reflector	white	215/215/110		>> 921643
20	3000	2050	>80	15	reflector	black	215/215/110		>> 921711
20	3000	2200	>80	60	reflector	white	215/215/110		>> 921483
20	3000	2200	>80	60	reflector	white	215/215/110		>> 425288
20	3000	2200	>80	60	reflector	white	215/215/110		>> 425004
20	3000	2200	>80	60	reflector	white	215/215/110		>> 425561
20	3000	2200	>80	60	reflector	black	215/215/110		>> 921575
20	3000	2200	>80	60	reflector	black	215/215/110		>> 425370
20	3000	2200	>80	60	reflector	black	215/215/110		>> 425097
20	3000	2200	>80	60	reflector	black	215/215/110		>> 425653
20	4000	2250	>80	60	reflector	white	215/215/110		>> 921209
20	4000	2250	>80	60	reflector	white	215/215/110		>> 913303
20	4000	2250	>80	60	reflector	white	215/215/110		>> 913006
20	4000	2250	>80	60	reflector	white	215/215/110		>> 913587
20	4000	2250	>80	60	reflector	black	215/215/110		>> 921292
20	4000	2250	>80	60	reflector	black	215/215/110		>> 913396
20	4000	2250	>80	60	reflector	black	215/215/110		>> 913099
20	4000	2250	>80	60	reflector	black	215/215/110		>> 913679

TIUNNE PLUS

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Colour rendering index	Beam angle [°]	Optics	Ring colour	Dimensions (H/W/T/S) [mm]	DIMM DALI	Index
24	3000	2400	>80	15	reflector	white	215/215/110		>> 425172
24	3000	2400	>80	15	reflector	black	215/215/110		>> 425240
24	3000	2400	>80	15	reflector	white	215/215/110		>> 425455
24	3000	2400	>80	15	reflector	black	215/215/110		>> 425523
24	3000	2400	>80	15	reflector	white	215/215/110		>> 425738
24	3000	2400	>80	15	reflector	black	215/215/110		>> 425806
24	4000	2450	>80	15	reflector	white	215/215/110		>> 913198
24	4000	2450	>80	15	reflector	black	215/215/110		>> 913266
24	4000	2450	>80	15	reflector	white	215/215/110		>> 913471
24	4000	2450	>80	15	reflector	black	215/215/110		>> 913549
24	4000	2450	>80	15	reflector	white	215/215/110		>> 913754
24	4000	2450	>80	15	reflector	black	215/215/110		>> 913822
24	4000	2450	>80	15	reflector	white	215/215/110		>> 921377
24	4000	2450	>80	15	reflector	black	215/215/110		>> 921445
24	3000	2400	>80	15	reflector	white	215/215/110		>> 921650
24	3000	2400	>80	15	reflector	black	215/215/110		>> 921728
24	3000	2500	>80	60	reflector	white	215/215/110		>> 921513
24	3000	2500	>80	60	reflector	white	215/215/110		>> 425318
24	3000	2500	>80	60	reflector	white	215/215/110		>> 425035
24	3000	2500	>80	60	reflector	white	215/215/110		>> 425592
24	3000	2500	>80	60	reflector	black	215/215/110		>> 921582
24	3000	2500	>80	60	reflector	black	215/215/110		>> 425387
24	3000	2500	>80	60	reflector	black	215/215/110		>> 425103
24	3000	2500	>80	60	reflector	black	215/215/110		>> 425660
24	4000	2600	>80	60	reflector	white	215/215/110		>> 921230
24	4000	2600	>80	60	reflector	white	215/215/110		>> 913334
24	4000	2600	>80	60	reflector	white	215/215/110		>> 913037
24	4000	2600	>80	60	reflector	white	215/215/110		>> 913617
24	4000	2600	>80	60	reflector	black	215/215/110		>> 921308
24	4000	2600	>80	60	reflector	black	215/215/110		>> 913402
24	4000	2600	>80	60	reflector	black	215/215/110		>> 913105
24	4000	2600	>80	60	reflector	black	215/215/110		>> 913686
28	3000	2700	>80	15	reflector	white	215/215/110		>> 425189
28	3000	2700	>80	15	reflector	black	215/215/110		>> 425257
28	3000	2700	>80	15	reflector	white	215/215/110		>> 425462
28	3000	2700	>80	15	reflector	black	215/215/110		>> 425530
28	3000	2700	>80	15	reflector	white	215/215/110		>> 425745
28	3000	2700	>80	15	reflector	black	215/215/110		>> 425813

TIUNNE PLUS

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Colour rendering index	Beam angle [°]	Optics	Ring colour	Dimensions (H/W/T/S) [mm]	DIMM DALI	Index
28	4000	2800	>80	15	reflector	white	215/215/110		>> 913204
28	4000	2800	>80	15	reflector	black	215/215/110		>> 913273
28	4000	2800	>80	15	reflector	white	215/215/110		>> 913488
28	4000	2800	>80	15	reflector	black	215/215/110		>> 913556
28	4000	2800	>80	15	reflector	white	215/215/110		>> 913761
28	4000	2800	>80	15	reflector	black	215/215/110		>> 913839
28	4000	2800	>80	15	reflector	white	215/215/110		>> 921384
28	4000	2800	>80	15	reflector	black	215/215/110		>> 921452
28	3000	2700	>80	15	reflector	white	215/215/110		>> 921667
28	3000	2700	>80	15	reflector	black	215/215/110		>> 921735
28	3000	2750	>80	60	reflector	white	215/215/110		>> 921520
28	3000	2750	>80	60	reflector	white	215/215/110		>> 425325
28	3000	2750	>80	60	reflector	white	215/215/110		>> 425042
28	3000	2750	>80	60	reflector	white	215/215/110		>> 425608
28	3000	2750	>80	60	reflector	black	215/215/110		>> 921599
28	3000	2750	>80	60	reflector	black	215/215/110		>> 425394
28	3000	2750	>80	60	reflector	black	215/215/110		>> 425110
28	3000	2750	>80	60	reflector	black	215/215/110		>> 425677
28	4000	2850	>80	60	reflector	white	215/215/110		>> 921247
28	4000	2850	>80	60	reflector	white	215/215/110		>> 913341
28	4000	2850	>80	60	reflector	white	215/215/110		>> 913044
28	4000	2850	>80	60	reflector	white	215/215/110		>> 913624
28	4000	2850	>80	60	reflector	black	215/215/110		>> 921315
28	4000	2850	>80	60	reflector	black	215/215/110		>> 913419
28	4000	2850	>80	60	reflector	black	215/215/110		>> 913112
28	4000	2850	>80	60	reflector	black	215/215/110		>> 913693
36	3000	3250	>80	15	reflector	white	215/215/110		>> 425196
36	3000	3250	>80	15	reflector	white	215/215/110	yes	>> 425202
36	3000	3250	>80	15	reflector	black	215/215/110		>> 425264
36	3000	3250	>80	15	reflector	black	215/215/110	yes	>> 425271
36	3000	3250	>80	15	reflector	white	215/215/110		>> 425479
36	3000	3250	>80	15	reflector	white	215/215/110	yes	>> 425486
36	3000	3250	>80	15	reflector	black	215/215/110		>> 425547
36	3000	3250	>80	15	reflector	black	215/215/110	yes	>> 425554
36	3000	3250	>80	15	reflector	white	215/215/110		>> 425752
36	3000	3250	>80	15	reflector	white	215/215/110	yes	>> 425769
36	3000	3250	>80	15	reflector	black	215/215/110		>> 425820
36	3000	3250	>80	15	reflector	black	215/215/110	yes	>> 425837

TIUNNE PLUS

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Colour rendering index	Beam angle [°]	Optics	Ring colour	Dimensions (H/W/T/S) [mm]	DIMM DALI	Index
36	4000	3350	>80	15	reflector	white	215/215/110		>> 913211
36	4000	3350	>80	15	reflector	white	215/215/110	yes	>> 913228
36	4000	3350	>80	15	reflector	black	215/215/110		>> 913280
36	4000	3350	>80	15	reflector	black	215/215/110	yes	>> 913297
36	4000	3350	>80	15	reflector	white	215/215/110		>> 913495
36	4000	3350	>80	15	reflector	white	215/215/110	yes	>> 913501
36	4000	3350	>80	15	reflector	black	215/215/110		>> 913563
36	4000	3350	>80	15	reflector	black	215/215/110	yes	>> 913570
36	4000	3350	>80	15	reflector	white	215/215/110		>> 913778
36	4000	3350	>80	15	reflector	white	215/215/110	yes	>> 913785
36	4000	3350	>80	15	reflector	black	215/215/110		>> 913846
36	4000	3350	>80	15	reflector	black	215/215/110	yes	>> 913853
36	4000	3350	>80	15	reflector	white	215/215/110		>> 921391
36	4000	3350	>80	15	reflector	white	215/215/110	yes	>> 921407
36	4000	3350	>80	15	reflector	black	215/215/110		>> 921469
36	4000	3350	>80	15	reflector	black	215/215/110	yes	>> 921476
36	3000	3250	>80	15	reflector	white	215/215/110		>> 921674
36	3000	3250	>80	15	reflector	white	215/215/110	yes	>> 921681
36	3000	3250	>80	15	reflector	black	215/215/110		>> 921742
36	3000	3250	>80	15	reflector	black	215/215/110	yes	>> 921759
36	3000	3400	>80	60	reflector	white	215/215/110		>> 921537
36	3000	3400	>80	60	reflector	white	215/215/110		>> 425332
36	3000	3400	>80	60	reflector	white	215/215/110		>> 425059
36	3000	3400	>80	60	reflector	white	215/215/110		>> 425615
36	3000	3400	>80	60	reflector	black	215/215/110		>> 921605
36	3000	3400	>80	60	reflector	black	215/215/110		>> 425400
36	3000	3400	>80	60	reflector	black	215/215/110		>> 425127
36	3000	3400	>80	60	reflector	black	215/215/110		>> 425684
36	3000	3400	>80	60	reflector	white	215/215/110	yes	>> 921544
36	3000	3400	>80	60	reflector	white	215/215/110	yes	>> 425349
36	3000	3400	>80	60	reflector	white	215/215/110	yes	>> 425066
36	3000	3400	>80	60	reflector	white	215/215/110	yes	>> 425622
36	3000	3400	>80	60	reflector	black	215/215/110	yes	>> 921612
36	3000	3400	>80	60	reflector	black	215/215/110	yes	>> 425417
36	3000	3400	>80	60	reflector	black	215/215/110	yes	>> 425134
36	3000	3400	>80	60	reflector	black	215/215/110	yes	>> 425691
36	4000	3500	>80	60	reflector	white	215/215/110		>> 921254
36	4000	3500	>80	60	reflector	white	215/215/110		>> 913358

TIUNNE PLUS

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Colour rendering index	Beam angle [°]	Optics	Ring colour	Dimensions (H/W/T/S) [mm]	DIMM DALI	Index
36	4000	3500	>80	60	reflector	white	215/215/110		>> 913051
36	4000	3500	>80	60	reflector	white	215/215/110		>> 913631
36	4000	3500	>80	60	reflector	black	215/215/110		>> 921322
36	4000	3500	>80	60	reflector	black	215/215/110		>> 913426
36	4000	3500	>80	60	reflector	black	215/215/110		>> 913143
36	4000	3500	>80	60	reflector	black	215/215/110		>> 913709
36	4000	3500	>80	60	reflector	white	215/215/110	yes	>> 921261
36	4000	3500	>80	60	reflector	white	215/215/110	yes	>> 913365
36	4000	3500	>80	60	reflector	white	215/215/110	yes	>> 913068
36	4000	3500	>80	60	reflector	white	215/215/110	yes	>> 913648
36	4000	3500	>80	60	reflector	black	215/215/110	yes	>> 921339
36	4000	3500	>80	60	reflector	black	215/215/110	yes	>> 913433
36	4000	3500	>80	60	reflector	black	215/215/110	yes	>> 913150
36	4000	3500	>80	60	reflector	black	215/215/110	yes	>> 913716

Card creation date: 24 January 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 469/2023; 469/2023