


17.45 FULL ELECTRIC















DIMENSIONS			TRANSMISSION		
Height	mm	2560	Transmission		electric
Width	mm	2360	Speed	km/h	25
Length	mm	6520	MOTOR		
Cabin width	mm	960	Transmission	kW	51 (S1)
VEIGHT			Hydraulic services	kW	23 (S1)
Weight	kg	12100	HYDRAULIC		
ETAILS			Pump type		gears pump
Number of extracting sections	nr	3	Hydraulic capacity	l/bar	120/250
Max capacity	kg	4500	Distribution		flow sharing
Max lifting height	m	16,4	OTHER		
Max horizontal boom extension	m	12,6	Joystick		hydraulic-electro proportio
Boom extension at max height	m	2,5	Cabin		Queen Cab
Swinging Angle	٥	144	Quick coupling		0
ANK CAPACITY			Front and rear LED lights		0
Hydraulic oil tank	I	150	Floating boom		0
CONNECTION FOR EQUIPMENT			Boom suspension		0
FH		•	Manual 6-way diverter		0
TYRES			PEB (Boom Electric Socket)		0
405/70 20		0	Front constant flow		0
405/70 24		0	Bucket mode		•
445/65 R22.5		•	SPECIAL FEATURES		
Turning radius	m	4	Air conditioning		0
BATTERIES AND CHARGERS			Forward buzzer avas		0
Battery		435V (105 Ah)	Farmatics		FULL (2-5 years)
Charging type	V	220 - 380 🚮			

POWER AND BATTERY CAPACITY	45 kW/h (105 Ah)
AUTONOMY STANDARD CYCLE INTENSIVE (eco mode)	UPTO 3,5 HOURS
AUTONOMY STANDARD CYCLE NOT INTENSIVE (eco mode)	UP TO 8 HOURS

CHARGERS		
STANDARD ON BOARD CHARGER	0-80%	4 h
POWER INPUT POWER OUTPUT 16 A	0-100%	6 h

^{*}This is a first draft of data, further verification is ongoing