

- **Highlights:**

- Face recognition/ Qr code/bluetooth/pincode/badge reader access

- high end design: choice between brushed aluminium and real brass

- 1 device for flush and surface mounted installation. Choose during installation!

- 3 specific software versions in 1 device: Villa, offices and apartments



# fasttel®

## Door Entry Systems

---



Villa theme



## Door Entry Systems

---



Apartment theme



## Door Entry Systems

---



B&B theme



Office or small apartment theme (1-10 buttons)



Qr code reader

- **Physical & Power**

Front panel: Glass and anodised aluminium/ brass

Display: 4 Inch, color TFT LCD, touchable

Camera: 2M pixels



## Door Entry Systems

Numeric keypad as option  
Gesture detection sensor: Support  
Wiegand port: Support

---

RS485 port: Support  
RF card reader: 13.56MHz & 125kHz, NFC  
Relays out: 2  
Inputs: 3  
BLE : Support  
Line out: 1  
Power out: 12V/1A (Max.)  
Ethernet port: RJ45, 10/100Mbps adaptive  
802.3at Power-over-Ethernet  
12V DC connector (if not using PoE+)  
IP rate: IP65  
Installation: Wall-mounted and flush mounted with 1 and the same frame.  
Dimension: 280x124x39mm surface mounted/ flush mounted  
Working Humidity: 10~90%  
Working Temperature: -20°C ~ +60°C  
Storage Temperature: -40°C ~ +70°C

- **Audio**

SIP v1 (RFC2543), SIP v2 (RFC3261)  
Narrowband audio codec: G.711a, G.711μ  
Wideband audio codec: G.722  
DTMF: In-band, out-of-band DTMF (RFC2833), SIP Info  
Echo Cancellation  
Voice Activation Detection  
Comfort Noise Generator

- **Video**

Sensor: 1/2.8", CMOS for main camera  
Pixels: CIF, QCIF, VGA, 4CIF, 720p, 1080p  
  
Video codec: H.264  
Video technology: HDR  
Video resolution: up to 1920x1080  
Max. image transfer rate: 1080p – 30fps  
Viewing angle: 125°(H) / 65°(V)  
Compatible to 3rd-Party-Video components, e.g. NVRs



## Door Entry Systems

---

- **Networking and Protocol**

Protocols support: IPv4, HTTP, HTTPS, FTP, SNMP, DNS, NTP, RTSP, RTP, TCP, UDP, ICMP, DHCP, ARP

- **Door Entry Feature**

Relays controlled individually by DTMF tones  
Multi-way Unlock: Face, IC/ID Card, PIN and BLE  
Camera permanently operational  
White balance: auto  
Minimum illumination: 0.1LUX

- **Deployment & Maintenance**

Auto-Provisioning  
Web management portal  
Web-based packet dump  
Configuration backup / restore  
Entry log export  
Access table export / import  
Firmware upgrade  
System logs (include door access logs)

- **Application Scenario**

Provides resident / visitor access control for buildings such as condominiums, apartment buildings, office buildings, gated communities and industrial buildings